



# Specification Sheet

## Lake Cable Part #: 144C

**Description:** 14 AWG 4 conductor 19 strand bare copper wire with PVC insulation, unshielded and overall PVC jacket for low-voltage electronic cable applications.

- 1. Conductor**
  - 1.1.AWG Size & Stranding: 14 AWG 19 Strands Class C
  - 1.2.Material: Annealed Bare Copper
  - 1.3.Conductor Count: 4 Conductors
- 2. Insulation**
  - 2.1.Material: Polyvinylchloride
  - 2.2.Wall Thickness: 0.009"
  - 2.3.Color Code: Black, Red, White, Green
- 3. Assembly**
  - 3.1.Nominal Lay Length: 4.50" LHL (2.66 Tw/Ft)
  - 3.2.Shield: N/A
  - 3.3.Drain Wire: N/A
- 4. Jacket**
  - 4.1.Material: Polyvinylchloride
  - 4.2.Wall Thickness: 0.015"
  - 4.3.Diameter: 0.251"
  - 4.4.Color: Gray
  - 4.5.Ripcord: Yes
  - 4.6.Weight: 68 Lbs/Mft
- 5. Markings**
  - 5.1.Type: Cable permanently identified via surface inkjet print
  - 5.2.Legend: LAKE CABLE E171203 14AWG 4C (UL) FPLR OR (UL) CL3R 75°C SUN RES  
"ROHS" FT-4
  - 5.3.Footage Markers: Yes
- 6. Standards**
  - 6.1.Refer to NEC (NFPA 70) article 725 and article 800 for installation guidelines
  - 6.2.UL listed as type CL3R per UL standard 13 and as type FPLR 75°C per UL standard 1424
  - 6.3.All materials used in the manufacture of this cable are RoHS compliant
  - 6.4.Recommended Operating Voltage: 300V
  - 6.5.Made in the USA

***ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION***