

PVC - SPT-1, SPT-2, SPT-3

Bonded Lamp Cord

UL: 60°C, 300V, VW-1

CSA: 60°C, 300V, FT1



IEWC Part Number	AWG	No. of Conductors	Stranding	Nominal Insulation Thickness		Nominal O.D.		Approx. Weight		UL Type	
				in	mm	in	mm	lbs/1k ft	kg/km		
SPT1802	18	2	41/34	0.030	0.8	0.110 x 0.215	2.8 x 5.5	17	25	SPT-1	
			41/34	0.045	1.1	0.140 x 0.265	3.6 x 6.7	14	21	SPT-2	
			41/34	0.060	1.5	0.170 x 0.330	4.3 x 8.4	33	49	SPT-3	
SPT1803		3	41/34	0.030	0.8	0.110 x 0.275	2.8 x 7.0	25	37	SPT-1	
			41/34	0.045	1.1	0.140 x 0.360	3.6 x 9.1	33	49	SPT-2	
			41/34	0.060	1.5	0.170 x 0.375	4.3 x 9.5	46	68	SPT-3	
SPT1602	16	2	65/34	0.045	1.1	0.155 x 0.285	3.9 x 7.2	34	51	SPT-2	
			65/34	0.060	1.5	0.180 x 0.345	4.6 x 8.8	42	62	SPT-3	
SPT1603		3	65/34	0.045	1.1	0.155 x 0.380	3.9 x 9.7	57	85	SPT-2	
			65/34	0.060	1.5	0.180 x 0.415	4.6 x 10.5	57	85	SPT-3	
SPT1402		14	2	41/30	0.080	2.0	0.235 x 0.420	6.0 x 10.7	66	98	SPT-3
SPT1403			3	41/30	0.080	2.0	0.235 x 0.505	6.0 x 12.8	92	137	SPT-3
SPT1202	12	2	65/30	0.095	2.4	0.285 x 0.490	7.2 x 12.5	96	143	SPT-3	
SPT1203		3	65/30	0.095	2.4	0.285 x 0.585	7.2 x 14.9	124	185	SPT-3	
SPT1003	10	3	105/30	0.110	2.8	0.445 x 0.700	11.3 x 17.8	237	353	SPT-3	

Notes

- Soft-annealed, bare copper conductor
- Polyvinyl chloride (PVC) insulation
- RoHS Compliant
- Standard insulation colors: black, brown, clear & white

Alternative Constructions

- 3 conductor with green ground
- Temperature range up to 105°C

Available Certifications

CSA: FT2

Applications

For use in heating & cooling, lighting and appliance applications. Rated for continuous use up to 60°C.