


# ÖLFLEX® CLASSIC 110/110 CY

Flexible Power and Control Cable; Number-Coded; Unshielded & Shielded



ÖLFLEX® CLASSIC 110 is a number-coded multi-conductor power and control cable for use in all electrical equipment in dry, damp, or wet conditions. It is a European-style cable, conforms to CE, and is available unshielded or shielded.

## Unshielded Construction

**Conductors:** Finely stranded bare copper

**Insulation:** PVC

**Jacket:** PVC; gray

## Shielded Construction

**Conductors:** Finely stranded bare copper

**Insulation:** PVC

**Shielding:** Gray PVC inner jacket; tinned copper braid (85% coverage)

**Jacket:** PVC; transparent

## Recommended Applications

Control systems; assembly lines; control panels; data processing equipment; European machinery

## Approvals



## Application Advantage

- Common European control cable
- Conforms to CE standards
- Available with inner jacket and tinned copper braid for EMI & RFI protection
- Pressure-extruded jacket for improved flexibility

Cable Attributes		page 640	
OIL	OR-01	FLAME	FR-02
MOTION	FL-01	MECH.	MP-01

Complete the Installation	
SKINTOP® Strain Relief	EPIC® Connectors
page 488	page 280

## Technical Data

<b>Minimum Bend Radius:</b>	- for installation: 4 x cable diameter - shielded: 6 x cable diameter	<b>Test Voltage:</b>	4000V
<b>Temperature Range:</b>	- for flexible use: -5°C to +70°C - for stationary use: -40°C to +80°C	<b>Conductor Stranding:</b>	Class 5 fine wire
<b>Nominal Voltage:</b>	300/500V	<b>Color Code:</b>	Black with white numbers, plus green/yellow ground
		<b>Approvals:</b>	Based on VDE 7030 CE & RoHS

If not otherwise specified, all values relating to the product are nominal values. Photographs are not to scale and are not true representations of the products in question. For current information go to our website.

ÖLFLEX® CLASSIC 110

Part Number	Number of Conductors (incl. ground)	Nominal Outer Diameter (in) (mm)		Copper Weight (lbs/mft)	Approx. Weight (lbs/mft)	SKINTOP® Non-Metallic PG Thread	Part Number	Number of Conductors (incl. ground)	Nominal Outer Diameter (in) (mm)		Copper Weight (lbs/mft)	Approx. Weight (lbs/mft)	SKINTOP® Non-Metallic PG Thread
<b>20 AWG (0.50 mm²)</b>							1119318	18	0.567	14.4	174	274	S1121
1119752*	2	0.189	4.8	6	24	S1107	1119325	25	0.665	16.9	242	376	S1121
1119003	3	0.201	5.1	10	28	S1107	1119334	34	0.764	19.4	329	501	S1129
1119004	4	0.224	5.7	13	36	S1107	1119341	41	0.839	21.3	397	602	S1129
1119005	5	0.244	6.2	16	42	S1107	1119350	50	0.925	23.5	484	732	S1129
1119007	7	0.264	6.7	23	54	S1109	1119365	65	1.051	26.7	629	940	S1136
1119012	12	0.350	8.9	39	88	S1111	<b>14 AWG (2.50 mm²)</b>						
1119018	18	0.413	10.5	58	126	S1113	1119952*	2	0.295	7.5	32	68	S1111
1119025	25	0.488	12.4	81	175	S1116	1119403	3	0.319	8.1	48	89	S1111
1119035	35	0.571	14.5	113	239	S1121	1119404	4	0.350	8.9	65	110	S1111
1119052	52	0.681	17.3	168	347	S1129	1119405	5	0.394	10.0	81	134	S1113
1119065	65	0.772	19.6	210	433	S1129	1119407	7	0.437	11.1	113	179	S1113
1119080	80	0.831	21.1	258	524	S1129	1119412	12	0.583	14.8	194	299	S1121
1119100	100	0.929	23.6	323	655	S1129	1119418	18	0.701	17.8	290	436	S1129
<b>18 AWG (1.00 mm²)</b>							1119425	25	0.819	20.8	403	598	S1129
1119852*	2	0.224	5.7	13	36	S1107	1119434	34	0.961	24.4	548	812	S1129
1119203	3	0.236	6.0	19	44	S1107	1119450	50	1.157	29.4	806	1179	S1136
1119204	4	0.256	6.5	26	53	S1109	<b>12 AWG (4 mm²)</b>						
1119205	5	0.280	7.1	32	63	S1111	1119503	3	0.390	9.9	77	135	S1113
1119207	7	0.315	8.0	45	85	S1111	1119504	4	0.425	10.8	103	167	S1113
1119212	12	0.413	10.5	77	138	S1113	1119505	5	0.476	12.1	129	198	S1116
1119218	18	0.500	12.7	116	215	S1116	1119507	7	0.528	13.4	181	274	S1116
1119225	25	0.579	14.7	161	274	S1121	<b>10 AWG (6 mm²)</b>						
1119234	34	0.673	17.1	219	370	S1121	1119603	3	0.461	11.7	116	194	S1116
1119241	41	0.740	18.8	265	444	S1129	1119604	4	0.512	13.0	155	245	S1116
1119250	50	0.811	20.6	323	536	S1129	1119605	5	0.571	14.5	194	300	S1121
1119265	65	0.929	23.6	419	694	S1129	1119607	7	0.630	16.0	271	403	S1121
1119280	80	0.996	25.3	516	841	S1136	<b>8 AWG (10 mm²)</b>						
1119300	100	1.114	28.3	645	1048	S1136	1119614	4	0.638	16.2	258	397	S1121
<b>16 AWG (1.50 mm²)</b>							<b>6 AWG (16 mm²)</b>						
1119902*	2	0.248	6.3	19	46	S1109	1119624	4	0.740	18.8	413	731	S1129
1119303	3	0.264	6.7	29	56	S1109	<b>4 AWG (25 mm²)</b>						
1119304	4	0.283	7.2	39	70	S1111	1119634	4	0.925	23.5	645	1063	S1129
1119305	5	0.319	8.1	48	86	S1111	<b>2 AWG (35 mm²)</b>						
1119307	7	0.350	8.9	68	112	S1111	1119644	4	1.039	26.4	903	1415	S1136
1119312	12	0.472	12.0	116	188	S1116	1119645	5	1.165	29.6	1129	1771	S1136

\* 2c cable does not include ground

ÖLFLEX® CLASSIC 110 CY

Part Number	Number of Conductors (incl. ground)	Nominal Outer Diameter (in) (mm)		Copper Weight (lbs/mft)	Approx. Weight (lbs/mft)	SKINTOP® MS-SC PG Thread	Part Number	Number of Conductors (incl. ground)	Nominal Outer Diameter (in) (mm)		Copper Weight (lbs/mft)	Approx. Weight (lbs/mft)	SKINTOP® MS-SC PG Thread
<b>20 AWG (0.50 mm²)</b>							1135305	5	0.406	10.3	84	126	53112230
1135003	3	0.287	7.3	31	56	53112220	1135307	7	0.445	11.3	100	159	53112240
1135004	4	0.311	7.9	37	67	53112220	1135312	12	0.583	14.8	188	264	53112250
1135005	5	0.331	8.4	44	75	53112220	1135318	18	0.677	17.2	261	362	53112260
1135007	7	0.350	8.9	54	89	53112220	1135325	25	0.791	20.1	360	501	53112260
1135012	12	0.445	11.3	93	136	53112240	<b>14 AWG (2.50 mm²)</b>						
1135018	18	0.524	13.3	105	194	53112240	1135403	3	0.406	10.3	98	129	53112230
1135025	25	0.598	15.2	168	254	53112250	1135404	4	0.445	11.3	112	157	53112240
<b>18 AWG (1.00 mm²)</b>							1135405	5	0.496	12.6	134	190	53112240
1135203	3	0.323	8.2	44	75	53112220	1135407	7	0.547	13.9	194	249	53112250
1135204	4	0.343	8.7	52	87	53112220	<b>12 AWG (4 mm²)</b>						
1135205	5	0.374	9.5	60	103	53112230	1135504	4	0.528	13.4	159	233	53112240
1135207	7	0.402	10.2	76	124	53112230	1135505	5	0.579	14.7	188	278	53112250
1135212	12	0.524	13.3	126	206	53112240	<b>10 AWG (6 mm²)</b>						
1135218	18	0.610	15.5	192	288	53112250	1135604	4	0.622	15.8	214	326	53112250
1135225	25	0.689	17.5	261	366	53112260	<b>8 AWG (10 mm²)</b>						
<b>16 AWG (1.50 mm²)</b>							1135614	4	0.748	19.0	375	494	53112260
1135902*	2	0.335	8.5	44	79	53112220	<b>6 AWG (16 mm²)</b>						
1135303	3	0.350	8.9	56	91	53112220	1135624	4	0.874	22.2	540	934	53112260
1135304	4	0.378	9.6	67	110	53112230							

\* 2c cable does not include ground

Recommended SKINTOP® assumes minimal OD variance. Additional configurations are available; please see our SKINTOP® section. If not otherwise specified, all values relating to the product are nominal values. For current information go to our website.