

LUTZE SILFLEX® (C) TPE Feedback, Shielded

Flexible Feedback Cable for Allen-Bradley® and other Systems



Application

- Incremental encoder cable and resolver cable for tacho sensor, brake sensor, speed sensor
- Cable design for harsh industrial environments and operating conditions with high noise level
- UL listed and NFPA 79 compliant
- Dry, damp and wet locations

Characteristics

- High active and passive interference resistance (EMC)
- Flexible for easy installation
- Specially formulated TPE jacket for superior oil resistance according to UL1581
- Resistant to many mineral & vegetable based cutting oils
- Non-wicking fillers
- Extended temperature range and premium durability
- Sunlight resistant
- Talc and Silicone free

Technical Data

Nominal Voltage	300V UL PLTC-ER 300V UL CM 600V UL AWM 90C
Test voltage	1.5 kV
Temperature range	-40°C to + 90°C static
Bending radius	6 x cable OD static
Burning behavior	Flame retardant per UL Vertical-Tray UL VW-1
Oil resistance	UL1581 4 days in Oil at 100°C 60 days in Oil at 75°C
Approvals	A1410001: UL PLTC-ER, meets NEC 725 Class I, II Div. 2 per NEC Art. 336, 392, 501, 502 A1410002: UL CM, meets NEC 800 Both: UL AWM Style 20626 CE RoHS REACH

Construction

- AWG conductor
- Flexible fine wire stranded tinned copper conductors
- Special PVC conductor insulation
- Conductors color-coded for specific system
- Shielded with foil tape, drain wire and tinned copper braid shield, optical coverage ≥ 85 %
- Extremely oil resistant TPE jacket
- Green jacket similar RAL 6018

Additional feedback cables for other systems available. Please contact us for further information.

Allen-Bradley® is a registered trademark.
Specifications are subject to change without prior notice

Part No.	Description No. of conductors	OD / Ø ca. mm	OD / Ø inches	Weight Lbs/Mft	Copper Lbs/Mft
----------	----------------------------------	------------------	------------------	-------------------	-------------------

For Allen-Bradley® System and similar

A1410001	(5x2xAWG22) BK/BKWH, RD/RDWH, GN/GNWH, GY/GYWH, OG/OGWH	10.0	0.395	102	40
A1410002	(1x2xAWG16+1x2xAWG22+6x2xAWG26) AWG16: GY/GYWH AWG22: OG/OGWH AWG26: BK/BKWH, RD/RDWH, GN/GNWH, BL/BLWH, BN/BNWH, YE/YEWH	11.8	0.465	143	54