


LUTZE TOP-T Fittings NPT

Plastic NPT



Characteristics

- Integrated strain relief
- Wide sealing and clamping range
- Easy to install
- Temperature range -20°C - +100°C/
-4°F - +212°F
- Max temporary temperature up to
+150°C/+300°F
- Protection class IP68

Specifications

Connecting thread	NPT
Material	Polyamide 6
Seal	CR Chloroprene Rubber
Color	Black RAL 9005 Gray RAL 7001

Item Specific Approvals

- UL Recognized (R) or UL Listed (L), as per table

Specifications are subject to change without prior notice

Part No.	Thread	Clamping Range Ø inches	Clamping Range Ø mm	TL mm	D/SW mm	TD mm	H mm	UL R / L
BLACK								
FPNPT38B	NPT 3/8"	0.197-0.394	5-10	15	22	17.14	29	R
FPNPT12B	NPT 1/2"	0.394-0.551	10-14	11	30.9	21.34	31	L
FPNPT34B	NPT 3/4"	0.511-0.709	13-18	15	33	26.67	37	L
FPNPT10B	NPT 1"	0.709-0.984	18-25	18	42	33.4	41	L
GRAY								
FPNPT38G	NPT 3/8"	0.197-0.394	5-10	15	22	17.14	29	R
FPNPT12G	NPT 1/2"	0.394-0.551	10-14	11	30.9	21.34	31	L
FPNPT34G	NPT 3/4"	0.511-0.709	13-18	15	33	26.67	37	L
FPNPT10G	NPT 1"	0.709-0.984	18-25	18	42	33.4	41	L
REDUCED CLAMPING RANGE								
FPNPT38B-R	NPT 3/8"	0.118-0.276	3-7	15	22	17.14	29	
FPNPT12B-R	NPT 1/2"	0.276-0.472	7-12	11	30.9	21.34	31	
FPNPT34B-R	NPT 3/4"	0.354-0.630	9-16	15	33	26.67	37	
FPNPT10B-R	NPT 1"	0.472-0.787	12-20	18	42	33.4	41	