


# LUTZE TOP-T Fittings Reducer

## Plastic Metric Reducer



Part No.	Thread G	Thread G1	SW mm	L mm	L1 mm
METRIC REDUCER					
<b>600550</b>	M20x1.5	M12x1.5	24	12	8
<b>600551</b>	M20x1.5	M16x1.5	24	12	8
<b>600553</b>	M25x1.5	M16x1.5	32	14	8
<b>600554</b>	M25x1.5	M20x1.5	32	14	8
<b>600557</b>	M32x1.5	M20x1.5	36	16	10
<b>600558</b>	M32x1.5	M25x1.5	36	16	10
<b>600561</b>	M40x1.5	M25x1.5	46	16	10
<b>600562</b>	M40x1.5	M32x1.5	46	16	10
<b>600565</b>	M50x1.5	M32x1.5	55	18	12
<b>600566</b>	M50x1.5	M40x1.5	55	18	12

### Metric Reducer Characteristics

- Reduction of threaded or clearance holes to smaller thread size
- Temperature range      -30°C - +100°C /  
   -22°F - +212°F
- Material                      Polyamide PA6 GF30
- Internal/External thread    Metric as per EN 60423
- Color                          Gray RAL 7035

Specifications are subject to change without prior notice