


LUTZE TOP-T Fittings Metric

Metal Metric



Characteristics

- Integrated strain relief
- Anti-twist design
- Wide sealing and clamping range
- Easy to install
- Temperature range -20°C - +100°C / -4°F - +212°F
- Protection class IP68

Fitting Specifications

Connecting thread	Metric as per EN 60423
Material	Brass, nickel plated
Clamping insert	Polyamide 6
Seal	CR Chloroprene Rubber
O-ring	NBR

Item Specific Approvals

- UL Recognized (R) or UL Listed (L) as per table
- Type 4X for UL Recognized and UL Listed items

Specifications are subject to change without prior notice

Part No.	Thread	Clamping Range Ø inches	Clamping Range Ø mm	TL mm	SW1 mm	SW2 mm	H mm	UL R / L
METRIC								
FMM12	M12x1.5	0.118-0.256	3-6.5	6	14	14	22	R
FMM16	M16x1.5	0.157-0.315	4-8	7	17	18	23	R
FMM20	M20x1.5	0.236-0.472	6-12	8	22	22	26.5	L
FMM25	M25x1.5	0.394-0.551	10-14	8	24	27	27.7	L
FMM32	M32x1.5	0.512-0.709	13-18	9	30	34	33	L
FMM40	M40x1.5	0.709-0.984	18-25	9	40	43	38	L
FMM50	M50x1.5	0.866-1.260	22-32	9	50	55	48	L
FMM63	M63x1.5	1.339-1.732	34-44	14	64	68	53	L
LONG THREAD								
FMM12-L	M12x1.5	0.118-0.256	3-6.5	12	14	14	22	
FMM16-L	M16x1.5	0.157-0.315	4-8	12	17	18	23	
FMM20-L	M20x1.5	0.236-0.472	6-12	12	22	22	26.5	
FMM25-L	M25x1.5	0.394-0.551	10-14	12	24	27	27.7	
FMM32-L	M32x1.5	0.512-0.709	13-18	15	30	34	33	
FMM40-L	M40x1.5	0.709-0.984	18-25	15	40	43	38	
FMM50-L	M50x1.5	0.866-1.260	22-32	15	50	55	48	
FMM63-L	M63x1.5	1.339-1.732	34-44	18	64	68	53	