


# LUTZE TOP-T Fittings Reducer

## Metal PG and Metric Reducer



### PG Reducer Characteristics

- Reduction of threaded or clearance holes to smaller thread size
- Temperature range -30°C - +100°C / -22°F - +212°F
- Reduction Brass, nickel plated
- Internal/External thread PG as per DIN 40430

### Metric Reducer Characteristics

- Reduction of threaded or clearance holes to smaller thread size
- Temperature range -30°C - +100°C / -22°F - +212°F
- Reduction Brass, nickel plated
- Internal/External thread Metric as per EN 60423

Part No.	Thread G	Thread G1	SW mm	L mm	L1 mm
<b>PG</b>					
<b>600400</b>	PG 9	PG 7	17	8.5	6
<b>600411</b>	PG 11	PG 7	20	8.5	6
<b>600401</b>	PG 11	PG 9	20	8.5	6
<b>600408</b>	PG 13.5	PG 9	22	9	6.5
<b>600402</b>	PG 13.5	PG 11	22	9	6.5
<b>600409</b>	PG 16	PG 9	24	9.5	6.5
<b>600410</b>	PG 16	PG 11	24	9.5	6.5
<b>600403</b>	PG 16	PG 13.5	24	9.5	6.5
<b>600413</b>	PG 21	PG 11	30	10	7
<b>600414</b>	PG 21	PG 13.5	30	10	7
<b>600404</b>	PG 21	PG 16	30	10	7
<b>600407</b>	PG 29	PG 16	39	11.5	8
<b>600405</b>	PG 29	PG 21	39	11.5	8
<b>600412</b>	PG 36	PG 21	50	12.5	9
<b>600406</b>	PG 36	PG 29	50	12.5	9
<b>600416</b>	PG 42	PG 36	57	14	10
<b>METRIC</b>					
<b>600220</b>	M16x1.5	M12x1.5	18	8.5	6.0
<b>600221</b>	M20x1.5	M12x1.5	24	9	6.5
<b>600222</b>	M20x1.5	M16x1.5	24	9	6.5
<b>600223</b>	M25x1.5	M16x1.5	28	10	7
<b>600224</b>	M25x1.5	M20x1.5	28	10	7
<b>600225</b>	M32x1.5	M20x1.5	34	11.5	8
<b>600226</b>	M32x1.5	M25x1.5	34	11.5	8
<b>600227</b>	M40x1.5	M25x1.5	45	11.5	8
<b>600228</b>	M40x1.5	M32x1.5	45	11.5	8
<b>600229</b>	M50x1.5	M32x1.5	55	14	10
<b>600230</b>	M50x1.5	M40x1.5	55	14	10

Specifications are subject to change without prior notice