

LUTZE Cablefix Vario

Modular Strain Relief System with Plastic or Aluminum Frame for Cable Assemblies



Part No.	Frame Type	Dimensions WxHxD mm	No. of Small VK Inserts	No. of Large VG Inserts
PLASTIC				
606052	KKLR1	136 x 71 x 30	4	2
606053	KKLR2	164 x 71 x 30	6	3
ALUMINUM				
606001	AKLR1	108 x 68 x 30	4	2
606002	AKLR2	148 x 68 x 30	6	3
606004	AKLR4	148 x 108 x 30	12	6
606005	AKLR5	188 x 78 x 30	8	4
606007	AKLR7	188 x 118 x 30	16	8

Characteristics

- Frame material
- Protection class

Polished Aluminum or
Polyamide 66 (GF30)
IP65

Small (VK) Insert Characteristics

- Material
- Temperature range
- Resistance

TPE
-40°C - +135°C,
-40°F - +275°F
UV, ozone, oils and fuels,
acids and dyes, solvents
and salt water

Part No.	Type Small VK	Clamping Range Ø mm	No of Holes
606150	VK0	SOLID	0
606151	VK4	4 – 4.5	14
606152	VK5	4.5 – 5.5	8
606153	VK6	5.5 – 6.5	8
606154	VK7	6.5 – 7.5	5
606155	VK8	7.5 – 8.5	5
606156	VK9	8.5 – 9.5	3
606157	VK10	9.5 – 10.5	3
606158	VK12	10.5 – 12.5	2
606159	VK14	12.5 – 14.5	2
606160	VK16	14.5 – 16.5	2

Large (VG) Insert Characteristics

- Material
- Temperature range
- Resistance

TPE
-40°C - +135°C,
-40°F - +275°F
UV, ozone, oils and fuels,
acids and dyes, solvents
and salt water

Part No.	Type Large VG	Clamping Range Ø mm	No of Holes
606200	VG0	SOLID	0
606201	VG18	16.5 – 18.5	2
606202	VG20	18.5 – 20.5	1
606203	VG22	20.5 – 22.5	1
606204	VG24	22.5 – 24.5	1
606205	VG26	24.5 – 26.5	1
606206	VG28	26.5 – 28.5	1
606207	VG30	28.5 – 30.5	1
606208	VG32	30.5 – 32.5	1
606209	VG34	32.5 – 34.5	1

Blanking Plug Characteristics

- Material

PA6 (GF15)
Gray

Part No.	Fits Insert Part No.	Type	OD - Ø mm	Length mm
606250	606151	BL4	4	30
606251	606152	BL5	5	30
606252	606153	BL6	6	30
606253	606154	BL7	7	30
606254	606155	BL8	8	30
606255	606156	BL9	9	30
606256	606157	BL10	10	30
606257	606158	BL12	12	30
606258	606159	BL14	14	30
606259	606160	BL16	16	30
606260	606201	BL18	18	30

Specifications are subject to change without prior notice