

# LUTZE Fittings Cablefix

## Cablefix



### Characteristics

- Integrated strain relief in one direction
- Easy to install: cable pushes easily into position, locks itself and it can no longer be pulled out unless the clamp is released
- An integrated seal protects up to IP55
- Individual cables can be easily loosened and replaced for troubleshooting, maintenance or retrofitting
- Mix & Match: interlocking seal allows for any combination of the three different cablefix versions to custom fit it to your application
- Blanking plugs are supplied to seal unused holes

### Fitting Specifications

Material	Polyamide PA
Temperature range	-30°C - +70°C / 22°F - +212°F
Halogen free	Yes
Burning behavior	Polyamide plate according to UL 94 V2
Silicone free	Yes
Enclosure wall thickness	maximum 3 mm
Protection class	IP55
Seal	NBR60 oil resistant

Specifications are subject to change without prior notice

Part No.	Type	Dimensions (WxHxD) mm	Cut out W x H mm	Number of Cables x Cable OD - Ø mm
<b>600320</b>	1xB/V	50.0 x 50.0 x 10.0	46 x 46	2 x 6.1-8.8 + 2 x 7.8-10.7
<b>600321</b>	1xS/A	50.0 x 50.0 x 10.0	46 x 46	8 x 3.8-6.3
<b>600347</b>	1xST	50.0 x 50.0 x 10.0	46 x 46	6 x 6.3-8.9

