

BMP®51 and BMP®53 Voice & Data Comm Material: B-427 Self-Laminating Vinyl Material

Features a clear, non-printable area that wraps around the cable and serves as an overlamine to the printed text. Offers superior resistance to abrasion, dirt, oils, solvents, and water.




Figure 42




Figure 42a (continuous)



Diagram	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Label Height B Inch (mm)	Write-On Area C Inch (mm)	Labels/Roll	Sized to Fit
Fig. 42	M-19-427	B-427	Vinyl	BK on WT	1.000 (25.40)	1.000 (25.40)	0.375 (9.53)	200	2 pair Fiber/Coaxial, Single/Multi-Mode
Fig. 42	M-102-427	B-427	Vinyl	BK on WT	0.500 (12.70)	1.250 (31.75)	0.375 (9.53)	200	CAT-6, 4 pair UTP Copper
Fig. 42	M-115-427	B-427	Vinyl	BK on WT	1.500 (38.10)	1.250 (31.75)	0.500 (12.70)	200	CAT-6, 4 pair UTP Copper
Fig. 42	M-103-427	B-427	Vinyl	BK on WT	1.000 (25.40)	1.250 (31.75)	0.500 (12.70)	200	CAT-6, 4 pair UTP Copper, Fiber, Coaxial
Fig. 42	M-29-427	B-427	Vinyl	BK on WT	0.500 (12.70)	1.500 (38.10)	0.500 (12.70)	360	CAT-6, 4 pair UTP Copper
Fig. 42	M-30-427	B-427	Vinyl	BK on WT	0.750 (19.05)	1.500 (38.10)	0.500 (12.70)	200	CAT-6, 4 pair UTP Copper
Fig. 42	M-31-427	B-427	Vinyl	BK on WT	1.000 (25.40)	1.500 (38.10)	0.500 (12.70)	200	CAT-6, 4 pair UTP Copper, Fiber, Coaxial
Fig. 42	M-31-427-YL	B-427	Vinyl	BK on YL	1.000 (25.40)	1.500 (38.10)	0.500 (12.70)	200	CAT-6, 4 pair UTP Copper, Fiber, Coaxial
Fig. 42	M-32-427	B-427	Vinyl	BK on WT	1.500 (38.10)	1.500 (38.10)	0.500 (12.70)	180	CAT-6, 4 pair UTP Copper, Fiber, Coaxial
Fig. 42	M-21-427	B-427	Vinyl	BK on WT	1.000 (25.40)	2.500 (63.50)	0.750 (19.05)	80	25 pair Copper, 4-12 pair Fiber, Coaxial
Fig. 42	M-21-427-YL	B-427	Vinyl	BK on YL	1.000 (25.40)	2.500 (63.50)	0.750 (19.05)	80	25 pair Copper, 4-12 pair Fiber, Coaxial
Fig. 42	M-116-427	B-427	Vinyl	BK on WT	1.500 (38.10)	2.500 (63.50)	0.750 (19.05)	80	25 pair Copper, 4-12 pair Fiber, Coaxial
Fig. 42	M-23-427	B-427	Vinyl	BK on WT	1.000 (25.40)	4.000 (101.60)	1.000 (25.40)	70	50 pair Copper, 24 pair Fiber, Backbone
Fig. 42	M-23-427-YL	B-427	Vinyl	BK on YL	1.000 (25.40)	4.000 (101.60)	1.000 (25.40)	70	50 pair Copper, 24 pair Fiber, Backbone
Fig. 42	M-33-427	B-427	Vinyl	BK on WT	1.500 (38.10)	4.000 (101.60)	1.000 (25.40)	70	50 pair Copper, 24 pair Fiber, Backbone
Fig. 42	M-34-427	B-427	Vinyl	BK on WT	1.500 (38.10)	6.000 (152.40)	1.500 (38.10)	40	100 pair Copper, 36 pair Fiber, Backbone
Continuous Self-Laminating Vinyl Material									
Fig. 42a	MC-1000-427	B-427	Vinyl	BK on WT	25 ft. (7.62 m)	1.000 (25.40)	0.375 (9.53)	1 roll (cont.)	CAT-6, 4 pair UTP Copper
Fig. 42a	MC-1500-427	B-427	Vinyl	BK on WT	25 ft. (7.62 m)	1.500 (38.10)	0.500 (12.70)	1 roll (cont.)	CAT-6, 4 pair UTP Copper

BMP®51 and BMP®53 Wire & Cable Material: Automation & Electrical Component ID

Various sizes, colors and label types for marking relays, solenoids, switches, drive motors, and other components.




Figure 29




Figure 33




Figure 46



Diagram	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Label Height B Inch (mm)	Labels/Roll
B-422 – Gloss Polyester Material							
Fig. 29	M-7-422	B-422	Polyester	BK on WT	0.500 (12.70)	0.500 (12.70)	280
Fig. 29	M-17-422	B-422	Polyester	BK on WT	1.000 (25.40)	0.500 (12.70)	360
Fig. 29	M-19-422	B-422	Polyester	BK on WT	1.000 (25.40)	1.000 (25.40)	200
Fig. 33	MC-1000-422	B-422	Polyester	BK on WT	1.000 (25.40)	25ft. (7.62m)	1 roll (cont.)
Fig. 29	M-29-422	B-422	Polyester	BK on WT	1.500 (38.10)	0.500 (12.70)	360
Fig. 29	M-30-422	B-422	Polyester	BK on WT	1.500 (38.10)	0.750 (19.05)	200
B-428 – Metallized Polyester Material							
Fig. 29	M-17-428	B-428	Metallized Polyester	BK on SV	1.000 (25.40)	0.500 (12.70)	360
Fig. 46	M-24-428-BB	B-428	Metallized Polyester	BK on SV	1.130 (28.70)	0.500 (12.70)	360
Fig. 29	M-30-428	B-428	Metallized Polyester	BK on SV	1.500 (38.10)	0.750 (19.05)	260
Fig. 29	M-29-428	B-428	Metallized Polyester	BK on SV	1.500 (38.10)	0.500 (12.70)	360
Fig. 29	M-20-428	B-428	Metallized Polyester	BK on SV	2.000 (50.80)	1.000 (25.40)	80
B-483 – Ultra Aggressive Polyester Material							
Fig. 29	M-61-483	B-483	Polyester	BK on WT	2.000 (50.80)	0.500 (12.70)	80
Fig. 29	M-20-483	B-483	Polyester	BK on WT	2.000 (50.80)	1.000 (25.40)	80
B-499 – Nylon Cloth Material							
Fig. 29	M-11-499	B-499	Nylon Cloth	BK on WT	0.750 (19.05)	0.500 (12.70)	220
Fig. 29	M-84-499	B-499	Nylon Cloth	BK on WT	0.900 (22.86)	0.500 (12.70)	200
Fig. 29	M-132-499	B-499	Nylon Cloth	BK on WT	1.250 (31.75)	1.500 (38.10)	160
Fig. 29	M-78-499	B-499	Nylon Cloth	BK on WT	1.900 (48.26)	1.000 (25.40)	100
B-595 – Indoor / Outdoor Vinyl Material							
Fig. 33	MC-1000-595-OR-BK	B-595	Vinyl	BK on OR	1.000 (25.40)	25 ft (7.62 m)	1 roll (cont.)