




## ezLINK™ Indoor/Outdoor Loose Tube Mining Cable

MSHA and tray cable



- Water Blocking Binders
- Armid Yarns
- Inner Jacket
- Central Strength Member
- Gel-Filled Buffer Tube Containing up to 12 Fibers
- Ripcords
- Outer Jacket



Versatile indoor-outdoor flame-rated fiber cables designed for the rigors of mining operations

### Overview

Prysmian's ezLINK™ indoor-outdoor loose tube mining Cable designs provide flame-rated network solutions for mines, mine shafts and other applications requiring elevated tensile and crush performance. This cable design marries Prysmian's proven loose tube construction with upgraded design elements to create a rugged cable for specialty applications. These cables utilize flexible gel-filled buffer tubes with Prysmian's extensive portfolio of single-mode and multimode optical fibers to meet the performance needs for non-traditional installations.

### Product Snapshot

- Applications** Rugged indoor-outdoor cable providing unsurpassed performance for applications involving placement in mines, mine shafts, or cable trays
- Constructions** Dielectric (dual jacket)
- Flame Rating** Riser (OFNR / FT4) / MSHA
- Fiber Count** 2 to 144
- Fiber Types** Single-mode (ESMF, bend-insensitive) multimode (62.5/125-OM1, 50/125-OM2+, OM3 and OM4)
- Performance** TIA/EIA-568, ANSI/ICEA S-104-696, UL-1666, CSA 22.2, Telcordia GR-409, Telcordia GR-20, US Dept of Labor MSHA, RoHS Compliant

### Features and Benefits

- Accepted by MSHA and Pennsylvania Bureau of Deep Mine Safety
- 4500 N tensile strength to support placement in vertical rise
- 4500 N crush rating for added reliability
- Flexible kink-resistant buffer tubes for routing and storage
- Available with bend-insensitive single-mode and multimode optical fibers
- Fiber identification using TIA standardized color coding
- Flame-retardant, violet outer jacket for easy identification



## ezLINK™ | Indoor/Outdoor Loose Tube Mining Cable

MSHA and tray cable

### ezLINK™ Indoor-Outdoor Riser Loose Tube Mining Cable | RLTM Series | OFNR/FT4

Fiber Count	Number of Buffer Tubes	Fibers Per Unit	Diameter inches (mm)	Cable Weight lb/kft (kg/km)	Bend Radius UNDER LOAD inches (cm)	Bend Radius NO LOAD inches (cm)	Vertical Rise Between Supports feet (m)
2 - 60	5	12	0.52 (13.2)	118 (176)	10.4 (26.4)	5.2 (13.2)	2568 (783)
62 - 72	6	12	0.55 (13.9)	128 (191)	11.0 (27.9)	5.5 (14.0)	2366 (721)
74 - 84	7	12	0.59 (15.1)	150 (223)	11.9 (30.2)	6.0 (15.1)	2027 (618)
86 - 96	8	12	0.63 (15.9)	166 (247)	12.6 (31.8)	6.3 (15.9)	1830 (558)
98 - 108	9	12	0.67 (17.0)	190 (282)	13.4 (34.0)	6.7 (17.0)	1603 (488)
110 - 120	10	12	0.69 (17.6)	202 (301)	13.9 (35.2)	7.0 (17.6)	1502 (458)
122 - 132	11	12	0.73 (18.5)	223 (332)	14.6 (37.0)	7.3 (18.5)	1361 (415)
134 - 144	12	12	0.76 (19.4)	247 (367)	15.3 (38.9)	7.7 (19.5)	1232 (375)

**Ordering Guide** The Prysmian Group part number incorporates several significant attributes involving cable design and optical performance. The appropriate part number can be configured using the process described below

**Example:** ezLINK™ loose tube mining cable | indoor-outdoor riser | gel-filled buffer tubes | dielectric (double jacket) | 12 62.5/125 multimode fibers per buffer tube | 48 fibers total (printed in feet)

<b>1</b> LENGTH MARKINGS	<b>2</b> PRODUCT FAMILY	<b>3</b> CONSTRUCTION	<b>4</b> FIBER GROUPING	<b>5</b> FIBER TYPE	<b>6</b> FIBER COUNT	<b>7</b> FIBER GRADE
F	RLTM	BLANK	12	G6	048	M2

CABLE INFORMATION	
<b>1</b> LENGTH MARKINGS	F = Feet or M = Meters
<b>2</b> PRODUCT FAMILY	RLTM = Mining Indoor-Outdoor Riser Dielectric (double jacket) 2 to 144 fibers Flame Rating: OFNR/FT4
<b>3</b> CONSTRUCTION	(blank) = Not available with interlock armor
<b>4</b> FIBER GROUPING	12 = 12f per unit or tube

FIBER INFORMATION					
<b>5</b> FIBER TYPE					
SINGLE-MODE					
HB = Single-Mode (ITU G.652 C & D) Low Water Peak					
ES = Enhanced Single-Mode (ITU G.652 C & D)					
CE = Corning™ SMF28e+ Single-Mode					
B1 = Bend-Insensitive Single-Mode (ITU G.657.A1 & G.652.D)					
B2 = Bend-Insensitive Single-Mode (ITU G.657.A2 & .B2, & G.652.D)					
MULTIMODE					
	Wavelength (nm)	Bandwidth (MHz)	1 GbE Dist (m)	10 GbE Dist (m)	
G6 = OM1 (62.5µm)	850/1300	200/500	300/550	33/___	
G5 = OM2+ BIF (50µm)	850/1300	700/500	800	150/___	
G3 = OM3 BIF (50µm)	850/1300	1500/500	1000	300/___	
G4 = OM4 BIF (50µm)	850/1300	3500/500	1100	550/___	
<b>6</b> FIBER COUNT					
002 to 144 fibers					
<b>7</b> FIBER GRADE					
SINGLE-MODE					
Attenuation (dB/km)	Wavelength (nm)	Fiber Type			
E1 = 0.40/0.40/0.30	1310/1383/1550	HB, ES, or CE			
E3 = 0.35/0.35/0.25	1310/1383/1550	HB, ES, CE, B1, or B2			
MULTIMODE					
Attenuation (dB/km)	Wavelength (nm)	Fiber Type			
M2 = 3.5/1.0	850/1300	OM1 (62.5µm)			
M3 = 3.0/1.0	850/1300	OM2+, OM3, OM4 (50µm)			
Other cable constructions and fiber performance grades available on request.					

© DRAKA & PRYSMIAN - Brands of The Prysmian Group. 2014 All Right Reserved. The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed correct at the time of issue. Prysmian Group reserves the right to amend any specifications without notice. These specifications are not contractually valid unless specifically authorized by Prysmian Group. Issued December 2014.

**Prysmian Group**  
 700 Industrial Drive | Lexington, SC 29072  
 +1-800-879-9862 | +1-800-669-0808 | website: [na.prysmiangroup.com/telecom](http://na.prysmiangroup.com/telecom)