

Irradiated XLPE - NEMA HP-6-L (MIL-DTL-16878/14, Type L)

Military Hook-up Wire

125°C, 600V

UL: VW-1



IEWC Part Number	AWG	Stranding	Nominal Insulation Thickness		Nominal O.D.		Approx. Weight	
			in	mm	in	mm	lbs/1k ft	kg/km
M16878/14-BDB	26	7/374	0.011	0.3	0.041	1.0	2	3
M16878/14-BEB	24	7/32	0.011	0.3	0.047	1.2	2	3
M16878/14-BEE		19/36	0.011	0.3	0.047	1.2	2	3
M16878/14-BFB	22	7/30	0.011	0.3	0.053	1.3	3	5
M16878/14-BFE		19/34	0.011	0.3	0.053	1.3	3	5
M16878/14-BGE	20	19/32	0.011	0.3	0.061	1.5	5	7
M16878/14-BHE	18	19/30	0.011	0.3	0.071	1.8	7	10
M16878/14-BJE	16	19/29	0.011	0.3	0.081	2.1	10	14
M16878/14-BKE	14	19/27	0.011	0.3	0.096	2.4	15	22

Notes

- Soft-annealed, tinned copper conductor
- Irradiated cross-linked polyethylene (XLPE) insulation
- RoHS Compliant
- A variety of insulations colors available

Applications

For use in aerospace & military and electronic applications. Rated for continuous use up to 125°C.