



® ATLAS WIRE CORPORATION
9525 RIVER STREET
SCHILLER PARK, ILLINOIS 60176
(847) 678-1210
(847) 678-1281 FAX
www.atlaswirecorp.com



ATLAS WIRE CORPORATION
REGISTERED TO ISO 9001
CERTIFICATE NO. A4894

MATERIAL SPECIFICATION SHEET

#20 7/28 TC .010" PVC
RoHS Compliant
MIL-16878/1 TYPE B
105c - 600 VOLTS

CONDUCTOR:	#20 7/28 TINNED COPPER 3/4" CONCENTRIC	
	NOMINAL O.D.	.038"
	APPROXIMATE CIRCULAR MILL AREA	1.118
	WEIGHT PER THOUSAND FEET	3.40#
	BASIC SPECIFICATION	ASTM B-8 ASTM B-286
PVC:	TEMPERATURE RATING	105c
	VOLTAGE RATING	600 VOLTS
	ELONGATION	300% AVG.
	SPECIFIC GRAVITY	1.34
	DUROMETER (SHORE)	47 (D)
	TENSILE STRENGTH	3000 PSI AVG
	SPARK TESTED	5,700 VOLTS
	OXYGEN INDEX	25
	BRITTLE POINT	-29c
	FINISHED O.D.	.058"
	WEIGHT PER 1,000 FEET	4.30#
REVISION:	MIL-DTL- 16878G -	PRINT REQUIRED*

* OUR STANDARD IS PRINTED, IF NO PRINTING IS PREFERRED
PLEASE CALL THAT OUT AT TIME OF ORDER.