

GeneralCable
#4/0AWG 125°C 600V



WIRE CONSTRUCTION

CONDUCTOR: #4/0AWG 550/24 ROPE (19X29/24) TINNED COPPER
 INSULATION: CROSS-LINKED POLYETHYLENE-.082" NOMINAL WALL
 DIAMETER: .757" ± .010"
 UL: AWM STYLE 3271 125°C 600V
 CSA: AWM XLPE FT1 125°C 600V
 MIL: MIL-W-16878/16 125°C 3000V
 RoHS: COMPLIANT
 NET WEIGHT: 813 LBS/1000 FT
 PRINT: *68A9378P0000 125C 600V 4/0AWG 550STRD STYLE 3271 RJ AWM
 GENERAL CABLE BRAND REX BRAND (WC) XP4/082550-166-GE/
 CSA AWM IA 125C 600V FT1/IAW MIL-W-16878/16"
 COLOR: GREEN WITH CO-EXTRUDED YELLOW STRIPE
 30% - 40% COVERAGE

REVISIONS	0	01/16/08	FIRST ISSUE	GeneralCable 1600 West Main Street, Willimantic, CT 06226-1128 <u>The Power of One</u>
REFERENCES	IEWC/GE 68A9378P0000			DRAWING NO: 12-1755
	GeneralCable P/N 376720.35.S1.04			DRAWN BY: CAD
				APPROVED BY: M. LAJEUNESSE
				THIS DRAWING IS THE PROPERTY OF GeneralCable AND SHALL NOT BE REPRODUCED, COPIED, OR USED AS BASIS FOR THE MANUFACTURE OR SALE OF THIS DESIGN WITHOUT THE PERMISSION OF GeneralCable