

TABLE I. Wire construction details.

PIN ^{1/}	Wire size	Stranding	Conductor		Conductor diameter (nominal) (inch)	Finished wire diameter (inch)	
			Material ^{2/} , ^{3/}	Coating		Min	Max
M16878/36BAA*	32	1 X 32	Copper	Tin	.0080	.024	.030
M16878/36CAA*	32	1 X 32	C.C. steel	Tin	.0080	.024	.030
M16878/36BAB*	32	7 X 40	Copper	Tin	.0100	.026	.032
M16878/36DAB*	32	7 X 40	H.S.C.A	Silver	.0100	.026	.032
M16878/36BBA*	30	1 X 30	Copper	Tin	.0100	.026	.032
M16878/36DBA*	30	1 X 30	H.S.C.A	Silver	.0100	.026	.032
M16878/36CBA*	30	1 X 30	C.C. steel	Tin	.0100	.026	.032
M16878/36BBB*	30	7 X 38	Copper	Tin	.0120	.026	.034
M16878/36DBB*	30	7 X 38	H.S.C.A	Silver	.0120	.028	.034
M16878/36BCA*	28	1 X 28	Copper	Tin	.0126	.028	.035
M16878/36DCA*	28	1 X 28	H.S.C.A	Silver	.0126	.029	.035
M16878/36CCA*	28	1 X 28	C.C. steel	Tin	.0126	.029	.035
M16878/36BCB*	28	7 X 36	Copper	Tin	.0150	.029	.037
M16878/36DCB*	28	7 X 36	H.S.C.A	Silver	.0150	.031	.037
M16878/36BDA*	26	1 X 26	Copper	Tin	.0159	.031	.038
M16878/36DDA*	26	1 X 26	H.S.C.A	Silver	.0159	.032	.038
M16878/36CDA*	26	1 X 26	C.C. steel	Tin	.0159	.032	.033
M16878/36BDB*	26	7 X 34	Copper	Tin	.0190	.032	.041
M16878/36DDB*	26	7 X 34	H.S.C.A	Silver	.0190	.035	.041
M16878/36BDE*	26	19 X 38	Copper	Tin	.0210	.035	.041
M16878/36DDE*	26	19 X 38	H.S.C.A	Silver	.0210	.035	.041
M16878/36BEA*	24	1 X 24	Copper	Tin	.0201	.035	.043
M16878/36DEA*	24	1 X 24	H.S.C.A	Silver	.0201	.036	.043
M16878/36CEA*	24	1 X 24	C.C. steel	Tin	.0201	.036	.043
M16878/36BEB*	24	7 X 32	Copper	Tin	.0240	.036	.047
M16878/36DEB*	24	7 X 32	H.S.C.A	Silver	.0240	.040	.047
M16878/36BEE*	24	19 X 36	Copper	Tin	.0260	.040	.047
M16878/36DEE*	24	19 X 36	H.S.C.A	Silver	.0260	.040	.047
M16878/36BFA*	22	1 X 22	Copper	Tin	.0253	.041	.048
M16878/36DFA*	22	1 X 22	H.S.C.A	Silver	.0253	.041	.048
M16878/36CFA*	22	1 X 22	C.C. steel	Tin	.0253	.041	.048
M16878/36BFB*	22	7 X 30	Copper	Tin	.0300	.046	.053
M16878/36DFB*	22	7 X 30	H.S.C.A	Silver	.0300	.046	.053
M16878/36BFE*	22	19 X 34	Copper	Tin	.0320	.046	.053
M16878/36DFE*	22	19 X 34	H.S.C.A	Silver	.0320	.046	.053
M16878/36BGA*	20	1 X 20	Copper	Tin	.0320	.048	.055