

**1. CONDUCTOR:**

- 1.1 Size and Material: 12 19/25 AWG silver-plated copper wire.
- 1.2 O.D.: .084" nom.

**2. INSULATION:**

- 2.1 Extruded silicone rubber.
- 2.2 Marking on the insulation: As per NEMA Standard.
- 2.3 O.D.: .185" nom.
- 2.4 Color: As per order (replace X in the part number and at the end of the description by 0-9 color code).

**3. PERFORMANCE:**

- 3.1 Voltage rating: 1000 VAC R.M.S.
- 3.2 Temperature rating: 200<sup>0</sup>C


**4. REFERENCES:**

- 4.1 NEMA Standards Publication No. HP 6.

**CUSTOMER APPROVAL**

Sign: \_\_\_\_\_

Date: \_\_\_\_\_

Engineering Change Notice No.								This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.	Done: <i>Daniel Curson</i>	 1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourind.com			
							Date: January 21, 2016						
							Verified: <i>David Lott</i>		Description: <b>HP 6-SS-BLEX</b>				
							Date: January 21, 2016						
<b>UNCONTROLLED DOCUMENT</b> A later revision of this specification may exist.									Size: <b>A</b>	Scale: ---	Page: 1 of 1	Code Ident. No: <b>57104</b>	Specification No.: <b>F00716-X</b>