

**1. CONDUCTOR:**

- 1.1 Size and Material: 6 AWG, 133 strands (19 x 7), silver-plated copper wire.
- 1.2 O.D.: .202" nom.

**2. INSULATION:**

- 2.1 Extruded silicone rubber.
- 2.2 Marking on the insulation: as per NEMA Standard.
- 2.3 O.D.: .339" nom.
- 2.4 Color: as per order (replace X in the part number and at the end of the description by 0-9 color code).

**3. PERFORMANCE:**

- 3.1 Voltage rating: 1000 VAC R.M.S.
- 3.2 Temperature rating: 200°C




**4. REFERENCES:**

- 4.1 NEMA Standards Publication No. HP 6.

**CUSTOMER APPROVAL**

Sign: \_\_\_\_\_

Date: \_\_\_\_\_

|   |  |   |   |            |              |                              |                                    |
|---|--|---|---|------------|--------------|------------------------------|------------------------------------|
| Engineering Change Notice No.   | This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited. | Done:      | <br>1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3<br>Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourind.com |            |              |                              |                                    |
|   |  | Date: October 8, 2010   |   |            |              |                              |                                    |
|   |  | Verified:  | Description:<br><br><b>HP 6-SS-BPLX</b>   |            |              |                              |                                    |
|   |  | Date: October 8, 2010   |   |            |              |                              |                                    |
| <b>UNCONTROLLED DOCUMENT</b><br>A later revision of this specification may exist. |  |   | Size: <b>A</b>  | Scale: --- | Page: 1 of 1 | Code Ident. No: <b>57104</b> | Specification No.: <b>F04861-X</b> |