

PTFE - SAE AS22759/10 (MIL-W-22759/10, Type LH)

Teflon® Military Hook-up Wire

260°C, 1000V



IEWC Part Number	AWG	Stranding	Nominal Insulation Thickness		Nominal O.D.		Approx. Weight	
			in	mm	in	mm	lbs/1k ft	kg/km
M22759/10-28	28	7/36	0.014	0.4	0.043	1.1	2	3
M22759/10-26	26	19/38	0.014	0.4	0.048	1.2	3	4
M22759/10-24	24	19/36	0.014	0.4	0.053	1.3	4	6
M22759/10-22	22	19/34	0.015	0.4	0.060	1.5	5	7
M22759/10-20	20	19/32	0.015	0.4	0.068	1.7	7	10
M22759/10-18	18	19/30	0.015	0.4	0.078	2.0	9	13
M22759/10-16	16	19/29	0.015	0.4	0.085	2.2	11	16
M22759/10-14	14	19/27	0.016	0.4	0.100	2.5	17	25
M22759/10-12	12	19/25	0.017	0.4	0.120	3.0	24	36
M22759/10-10	10	37/26	0.019	0.5	0.145	3.7	36	54
M22759/10-8	8	133/29	0.025	0.6	0.212	5.4	66	98

Teflon is a registered trademark of DuPont Corporation

Notes

- Soft-annealed, nickel-plated copper conductor
- Polytetrafluoroethylene (PTFE) insulation
- A variety of insulation colors available

Applications

For use in aerospace & military and electronic applications. Rated for continuous use up to 260°C.