


PTFE - SAE AS22759/11 (MIL-W-22759/11, Type RC)

Teflon® Military Hook-up Wire

200°C, 600V



IEWC Part Number	AWG	Stranding	Nominal Insulation Thickness		Nominal O.D.		Approx. Weight	
			in	mm	in	mm	lbs/1k ft	kg/km
M22759/11-28	28	7/36	0.009	0.2	0.033	0.8	2	3
M22759/11-26	26	19/38	0.010	0.3	0.038	1.0	2	3
M22759/11-24	24	19/36	0.010	0.3	0.043	1.1	3	4
M22759/11-22	22	19/34	0.009	0.2	0.049	1.2	4	6
M22759/11-20	20	19/32	0.010	0.3	0.058	1.5	6	9
M22759/11-18	18	19/30	0.010	0.3	0.068	1.7	8	12
M22759/11-16	16	19/29	0.010	0.3	0.075	1.9	10	15
M22759/11-14	14	19/27	0.011	0.3	0.090	2.3	15	22
M22759/11-12	12	19/25	0.013	0.3	0.111	2.8	23	34
M22759/11-10	10	37/26	0.015	0.4	0.139	3.5	35	52
M22759/11-8	8	133/29	0.019	0.5	0.204	5.2	66	98

Teflon is a registered trademark of DuPont Corporation

Notes

- Soft-annealed, silver-plated copper conductor
- Polytetrafluoroethylene (PTFE) insulation
- A variety of insulation colors available

Applications

For use in aerospace & military and electronic applications. Rated for continuous use up to 200°C.