

XLETFE - SAE AS22759/32 (MIL-W-22759/32, Type SB)

Tefzel® Military Hook-up Wire

150°C, 600V



IEWC Part Number	AWG	Stranding	Nominal O.D.		Approx. Weight	
			in	mm	lbs/1k ft	kg/km
M22759/32-30	30	7/38	0.024	0.6	1	1
M22759/32-28	28	7/36	0.027	0.7	1	1
M22759/32-26	26	19/38	0.032	0.8	1	1
M22759/32-24	24	19/36	0.037	0.9	2	3
M22759/32-22	22	19/34	0.043	1.1	3	4
M22759/32-20	20	19/32	0.050	1.3	4	6
M22759/32-18	18	19/32	0.060	1.5	7	10
M22759/32-16	16	19/29	0.068	1.7	8	12
M22759/32-14	14	19/27	0.085	2.2	13	19
M22759/32-12	12	37/28	0.103	2.6	20	30

Tefzel is a registered trademark of DuPont Corporation

Notes

- Soft-annealed, tinned copper conductor
- Chemically cross-linked ethylene tetrafluoroethylene (XLETFE) insulation
- A variety of insulation colors available

Alternative Constructions

- Irradiated cross-linked ethylene tetrafluoroethylene (XLETFE) insulation

Applications

For use in aerospace & military and electronic applications. Rated for continuous use up to 200°C.