

XLETFE/XLETFE - SAE AS22759/43 (MIL-W-22759/43, Type SP)

Tefzel® Military Hook-up Wire

200°C, 600V



IEWC Part Number	AWG	Stranding	Nominal O.D.		Approx. Weight	
			in	mm	lbs/1k ft	kg/km
M22759/43-26	26	19/38	0.040	1.0	2	3
M22759/43-24	24	19/36	0.045	1.1	2	3
M22759/43-22	22	19/34	0.050	1.3	3	4
M22759/43-20	20	19/32	0.058	1.5	5	7
M22759/43-18	18	19/30	0.070	1.8	7	10
M22759/43-16	16	19/29	0.077	2.0	9	13
M22759/43-14	14	19/27	0.094	2.4	14	21
M22759/43-12	12	37/28	0.111	2.8	21	31
M22759/43-10	10	37/26	0.134	3.4	32	48
M22759/43-8	8	133/29	0.195	5.0	62	92
M22759/43-6	6	133/27	0.241	6.1	95	141
M22759/43-4	4	133/25	0.310	7.9	150	223
M22759/43-2	2	665/30	0.405	10.3	239	356
M22759/43-1	1	817/30	0.445	11.3	290	432
M22759/43-01	1/0	1045/30	0.485	12.3	377	561
M22759/43-02	2/0	1330/30	0.545	13.8	487	725

Tefzel is a registered trademark of DuPont Corporation

Notes

- Soft-annealed, silver-plated copper conductor
- Chemically cross-linked ethylene tetrafluoroethylene (XLETFE) dual pass insulation
- A variety of insulation colors available

Alternative Constructions

- Irradiated cross-linked ethylene tetrafluoroethylene (XLETFE) insulation

Applications

For use in aerospace & military and electronic applications. Rated for continuous use up to 200°C.