

PTFE - SAE AS22759/5 (MIL-W-22759/5, Type VA)

Teflon® Military Hook-up Wire

200°C, 600V



IEWC Part Number	AWG	Stranding	Nominal Insulation Thickness		Nominal O.D.		Approx. Weight	
			in	mm	in	mm	lbs/1k ft	kg/km
M22759/5-24	24	19/36	0.026	0.7	0.075	1.9	6	9
M22759/5-22	22	19/34	0.027	0.7	0.085	2.2	8	12
M22759/5-20	20	19/32	0.028	0.7	0.095	2.4	10	15
M22759/5-18	18	19/30	0.031	0.8	0.110	2.8	14	21
M22759/5-16	16	19/29	0.035	0.9	0.125	3.2	18	27
M22759/5-14	14	19/27	0.037	0.9	0.143	3.6	25	37
M22759/5-12	12	19/25	0.038	1.0	0.160	4.1	35	52
M22759/5-10	10	37/26	0.035	0.9	0.179	4.5	48	71
M22759/5-8	8	133/29	0.043	1.1	0.248	6.3	84	125
M22759/5-6	6	133/27	0.047	1.2	0.300	7.6	126	188
M22759/5-4	4	133/25	0.048	1.2	0.355	9.0	188	280

Teflon is a registered trademark of DuPont Corporation

Notes

- Soft-annealed, silver-plated copper conductor
- Mineral filled polytetrafluoroethylene (PTFE) insulation
- A variety of insulation colors available

Applications

For use in aerospace & military and electronic applications. Rated for continuous use up to 200°C.