

# PTFE - SAE AS22759/6 (MIL-W-22759/6, Type WA)

Teflon® Military Hook-up Wire

260°C, 600V



IEWC Part Number	AWG	Stranding	Nominal Insulation Thickness		Nominal O.D.		Approx. Weight	
			in	mm	in	mm	lbs/1k ft	kg/km
<b>M22759/6-24</b>	24	19/36	0.026	0.7	0.075	1.9	6	9
<b>M22759/6-22</b>	22	19/34	0.027	0.7	0.085	2.2	8	12
<b>M22759/6-20</b>	20	19/32	0.028	0.7	0.095	2.4	10	15
<b>M22759/6-18</b>	18	19/30	0.031	0.8	0.110	2.8	14	21
<b>M22759/6-16</b>	16	19/29	0.035	0.9	0.125	3.2	18	27
<b>M22759/6-14</b>	14	19/27	0.037	0.9	0.143	3.6	25	37
<b>M22759/6-12</b>	12	19/25	0.038	1.0	0.160	4.1	35	52
<b>M22759/6-10</b>	10	37/26	0.035	0.9	0.179	4.5	48	71
<b>M22759/6-8</b>	8	133/29	0.042	1.1	0.248	6.3	84	125
<b>M22759/6-6</b>	6	133/27	0.046	1.2	0.300	7.6	126	188
<b>M22759/6-4</b>	4	133/25	0.047	1.2	0.355	9.0	180	268

Teflon is a registered trademark of DuPont Corporation

## Notes

- Soft-annealed, nickel-plated copper conductor
- Mineral filled, polytetrafluoroethylene (PTFE) insulation
- A variety of insulation colors available

## Applications

For use in aerospace & military and electronic applications. Rated for continuous use up to 260°C.