

Rev:	Change:	By:	Date:



Construction:		OD (In.)
1 Conductor:	20 19/32 Nickel Plated Copper(NPC)	0.0377" nom.
Insulation:	Extruded Polytetrafluorethylene (PTFE)	0.058" nom.
Color:	Per Order	
Surface Print:	M22759/12-20 27478	

Physical Characteristics		
1 Weight per 1000':	5.3	Lbs. nom.
2 Operating temperature range:	200 Max	°C
3 RoHS compliance:	Complies with RoHS (Directive 2002/95/EC)	

Harbour Industries

4744 Shelburne Rd. Ph.: 802-985-3311 Shelburne, VT 05482 Fax: 802-985-0726 www.harbourind.com	Drawn By:	<i>S.K. Wooster</i>	This drawing contains proprietary information and is issued in strict confidence and shall not be copied, reproduced, transmitted or disclosed to any third party either wholly or in part without prior written approval of Harbour Industries . All copies outside of the Harbour Industries CAD system are Uncontrolled .					
	Approved By:	<i>M.T. Piner</i>						
	Date:	9/10/12	Part Number:	J1168-** Designates Color	Rev:	N/A	Sheet:	1 of 1
	Scale:	None	Drawing Name:	M22759/12-20	Drawing Number:	091012		