ZONE	REL. NO. CHANGE NO.	SYM. CHG.	SYM. REV.	REVISIONS DESCRIPTION	DATE	D'MAN.	APP'D.
	RDC 2753		B	ADDED TELEDYNE TO SOURCES, ADDED WIRE COLORS.	12/19/86	STS	12/22/86

1. VENDOR IS RESPONSIBLE FOR CERTIFYING THAT EACH CABLE SHIPMENT WILL BE FREE OF KINKING & OTHER DEFECTS.

FOR QUOTE PURPOSES ONLY PURCHASING

CABLE, SPECIAL PURPOSE, ELECTRICAL (TRIPLEX)

CONFORMS TO: MIL-C-27500-20RA3N06 (SEE SPECIAL INSTRUCTIONS BELOW).

CONSISTS OF: 3 PCS MIL-W-22759/3-20 WIRE TWISTED & SHIELDED WITH NICKEL COATED COPPER (SEE SPECIAL INSTRUCTIONS BELOW).

INNER INSULATION: TFE GLASS TAPE, SKIVED TFE, DIP FUSED GLASS - TFE, TFE TAPE (WHITE).

OUTER INSULATION: TFE TAPE WRAPPED JACKET, FUSED TFE OVERLAP (WHITE).

TEMPERATURE RATING: 260°C.

SPECIAL INSTRUCTIONS: THE FINISHED (INSULATION) DIAMETER OF EACH MIL-W-22759/3-20 WIRE TO BE .081±.002. INSULATION COLORS TO BE SOLID WHITE, SOLID BLUE, & SOLID ORANGE.

AUTHORIZED SOURCES OF SUPPLY

TENSOLITE CO.

VENDOR P/N: 20581/50225PT-3

TELEDYNE THERMATICS

VENDOR P/N: 12688

THE MATERIAL CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO CO-OPERATIVE INDUSTRIES AND SHALL NOT TO BE DISCLOSED OR REPRODUCED IN ANY PART WITHOUT THE EXPRESSED WRITTEN CONSENT FROM AN AUTHORIZED CO-OPERATIVE INDUSTRIES REPRESENTATIVE.

DO NOT SCALE - WORK TO DIMENSIONS GIVEN.

PROD. CLASS 61

TOLERANCES				
DECIMALS (2 PLACES) ±.01	DECIMALS (3 PLACES) ±.005	ANGLES ±2°	DRAWING REQUEST 11942	DRAWN S.T.SZYMANSKI DATE 10/14/80
MATERIAL SPEC.			STD. PROCEDURE ☐ YES ☐ NO	CHECKED / Q.C. / MFG. ENGRG.
PROCESS SPEC.			NEXT ASSEMBLY 600009	PROJ. ENGRG. D.A.SOMERS / ISSUED.
ENGINEERING SPEC.			CUSTOMER REFERENCE:	

Co-Operative Industries

CABLE, SPECIAL PURPOSE ELECTRICAL - #20 AWG

W028XD9

CODE IDENT. NO.	SIZE	PART NO	REV.
81482	A	60182	B

SCALE | WT. | REF. | SHEET OF

52114

60182 B