



## Heyco® -Tite Snap-In-2® Liquid Tight Cordgrips

### Straight-Thru, Snap-In Hubs

For Panels from .062" (1,6 mm) to .125" (3,2 mm) Thick



*The Ultimate in Liquid Tight Strain Relief Protection*

**NO LOCKNUT REQUIRED!**

- Easy installation—unique fingers securely snap into a range of panel thicknesses – up to .125" (3,2 mm) – with no tools or locknuts required.
- Sealing flange prevents sealing washer displacement due to water velocity to ensure a liquid tight IP 65 seal.
- Eliminate need for locknut or threaded hole to achieve liquid tight seal at panel; perfect for low clearance installation where locking nut access is limited.
- Ratchet design of sealing nut assembly provides superior anti-vibration and ensures a firm grip on the cable.
- Foam washer included.
- Rotation prevented when used in “Double D” mounting holes.
- Available in multiple sizes for flexible cord diameters ranging from .065" (1,7 mm) to 1.000" (25,4 mm).
- We recommend using the fitting with the smallest maximum diameter that will fit your application.
- Consult Heyco for cordgrips molded in other colors.

CABLE DIA. RANGE				PART NO.	DESCRIPTION	UL or IEC	PANEL DIMENSIONS					
Minimum		Maximum					Black	A Mounting Hole Dia.		B To Prevent Rotation		C Max. O.A. Length
in.	mm.	in.	mm.			in.	mm.	in.	mm.	in.	mm.	
.065	1,7	.210	5,3	<b>M3802</b>	LTRSCG 500	UL	.500	12,7	.450	11,4	1.21	30,7
.115	2,9	.250	6,4	<b>M3800</b>	LTSCG 500							
.065	1,7	.230	5,8	<b>M3808</b>	LTRSCG 625	UL	.625	15,9	.550	14,0	1.30	33,0
.105	2,7	.315	8,0	<b>M3806</b>	LTSCG 625							
.069	1,8	.250	6,4	<b>M3814</b>	LTRSCG 750	UL	.750	19,1	.660	16,8	1.48	37,6
.230	5,8	.395	10,0	<b>M3812</b>	LTSCG 750							
.095	2,4	.260	6,6	<b>M3820</b>	LTRSCG 875	UL	.875	22,2	.770	19,6	1.46	37,1
.170	4,3	.450	11,4	<b>M3818</b>	LTSCG 875							
.180	4,6	.440	11,2	<b>M3826</b>	LTRSCG 1000	UL	1.000	25,4	.875	22,2	1.62	41,1
.260	6,6	.546	13,9	<b>M3824</b>	LTSCG 1000							
.250	6,4	.485	12,3	<b>M3838</b>	LTRSCG 1125	UL	1.125	28,6	1.000	25,4	1.75	44,5
.485	12,3	.709	18,0	<b>M3836</b>	LTSCG 1125							
.490	12,4	.787	20,0	<b>M3844</b>	LTRSCG 1250	UL	1.250	31,8	1.125	28,6	2.05	52,1
.590	15,0	.920	23,4	<b>M3842</b>	LTSCG 1250							
.490	12,4	.787	20,0	<b>M3850</b>	LTRSCG 1375	UL	1.375	34,9	1.250	31,8	2.05	52,1
.590	15,0	1.000	25,4	<b>M3848</b>	LTSCG 1375							

Standard color black.



Quick Specs

Material	Nylon 6/6 w/Buna N or TPE Sealing Gland
Certifications	UL Recognized under Components Program of Underwriters' Laboratories File E51579 CSA Certified by Canadian Standard Association File 93876C
Flammability Rating	94V-2
Temperature Range	Static -40°F (-40°C) to 239°F (115°C) Dynamic -4°F (-20°C) to 212°F (100°C)
IP Rating	IP 65