# **Detailed Specifications & Technical Data**



ģ

## 8529 Hook-up/Lead - (Type MW) MIL-W-76C-PVC

For more Information please call

1-800-Belden1



### **General Description:**

Tinned copper, PVC insulation, medium wall. The extruded PVC insulation is flame and ozone resistant. Inert to most chemicals, oils, and solvents. Covers single cond., PVC insulated hook-up wire for internal wiring of electrical and electronic equipment.

Physical Characteristics (Overall)	
Conductor	
AWG:	
# Conductors AWG Stranding Conductor Material	
1 20 Solid TC - Tinned Copper	
Total Number of Conductors:	1
Insulation Insulation Material:	
Insulation Material         Wall Thickness (in.)           PVC - Polyvinyl Chloride         .017	
Overall Insulation Overall Cable	
Overall Nominal Diameter:	0.066 in.
Applicable Specifications and Agency Compliance ( Applicable Standards & Environmental Programs	Overall)
EU Directive 2011/65/EU (ROHS II):	Yes
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	10/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Military Specification:	MIL-W-76C
MIL Spec Rating:	1000 V, 80°C
Plenum/Non-Plenum	
Plenum (Y/N):	No

## Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
8529 0021000	1,000 FT	6.000 LB	RED	P	20 SOL PVC RED
8529 0041000	1,000 FT	6.000 LB	YELLOW	Р	20 SOL PVC YEL
8529 0051000	1,000 FT	6.000 LB	GREEN, DARK	Р	20 SOL PVC GRN
8529 009100	100 FT	0.600 LB	WHITE		20 SOL PVC WHT
8529 0091000	1,000 FT	6.000 LB	WHITE	P	20 SOL PVC WHT
8529 010100	100 FT	0.600 LB	BLACK		20 SOL PVC BLK
8529 0101000	1,000 FT	6.000 LB	BLACK	P	20 SOL PVC BLK
8529 0131000	1,000 FT	6.000 LB	BLUE, DARK	P	20 SOL PVC DBLU

Notes: P = STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M' FOR1 OR 2 STRIPES. 10000' MINIMUM ORDER FOR COLOR COMBINATION.PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL

# **Detailed Specifications & Technical Data**



## ENGLISH MEASUREMENT VERSION

## 8529 Hook-up/Lead - (Type MW) MIL-W-76C-PVC

Revision Number: 1 Revision Date: 05-14-2007

© 2015 Belden, Inc All Rights Reserved

All hough Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, is deleden's knowledge, information, and belief at the date of its publication. The information provided to the best of Belden's howledge, information, and belief or the one that it becomes a part of. This Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product tusers are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.