

## MB3A10A2C2

Article Number: 151-00331

Acrylic Adh. Bases, .14" Max tie width, .75" Length/Width, .12" Hole Dia., PA66, White, 100/pkg



Download spec sheet

### Base Data

**Local Order Number** MB3A10A2C2

**Type** MB3A

**Color** White (WH)

- Features and Benefits**
- For use with 18 and 30 pound cable ties to provide stability when securing bundles.
  - Secures with acrylic based adhesive backing for heavy bonding applications
  - Can also be secured using two or four screws; providing multiple options.
  - 4 way opening allows cable ties to be installed parallel or perpendicular to wire bundles.

**Product Description** HellermannTyton adhesive fastened mounting bases are used with 18 through 150 pound cable ties to provide stability when securing bundles. The mounts are installed using the adhesive backing and/or by securing two or four screws. The 4 way opening allows the cable ties to be inserted parallel or perpendicular to the wire bundles.

**Short Description** Acrylic Adh. Bases, .14" Max tie width, .75" Length/Width, .12" Hole Dia., PA66, White, 100/pkg

### Product Dimensions

**Length L (Imperial)** 0.75 "

**Length L (Metric)** 19.0 mm

**Fixation Method** Screw Mounting and Adhesive

**Width W (Imperial)** 0.75 "

**Width W (Metric)** 19.0 mm

**Cable Tie Width Max. (Imperial)** 0.14 "

**Cable Tie Width Max. (Metric)** 3.6 mm

**Height H (Imperial)** 0.19 "

**Height H (Metric)** 4.8 mm

**Mounting Hole Diameter D (Imperial)** 0.12 "

**Mounting Hole Diameter D (Metric)** 3.0 mm

**Mounting Hole Centers (Imperial)** 0.52 "

**Mounting Hole Diameter D Max. (Metric)** 3.0 mm

**Mounting Hole Diameter D Min. (Metric)** 3.0 mm

### Logistics and Packaging

**Quantity Per** bag

**Package Quantity (Metric)** 100

**Carton Quantity** 10000

### Material and Specifications

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Adhesive</b>	Acrylate with base of acrylic foam
<b>Flammability</b>	UL94 V2 (excluding adhesive)
<b>Operating Temperature</b>	-40°F to +185°F (-40°C to +85°C)
<b>ROHS Compliant</b>	Yes
<b>UL Listed (US and Canada)</b>	No
<b>UL Recognized (US and Canada)</b>	Yes