

MB4SHA10H4



Article Number: 151-29206

Adhesive Bases, .18" Max tie width, .15" Hole Dia., 1.12" Length/Width, PA66, White, 500/pkg



Download spec sheet

Base Data

Local Order Number	MB4SHA10H4
Type	MB4SHA
Color	White (WH)
Features and Benefits	<ul style="list-style-type: none"> • 2-way opening for use with 18 through 50 pound cable ties to provide stability when securing bundles. • Secures using the adhesive backing and/or with one screw.
Product Description	HellermannTyton's 2 way, adhesive fastened mounting base is used with 18 through 50 pound cable ties to provide stability when securing bundles. The mounts are installed using the adhesive backing and/or by inserting one screw through the center of the mount.
Short Description	Adhesive Bases, .18" Max tie width, .15" Hole Dia., 1.12" Length/Width, PA66, White, 500/pkg

Product Dimensions

Length L (Imperial)	1.12 "
Length L (Metric)	28.3 mm
Fixation Method	Screw Mounting and Adhesive
Width W (Imperial)	1.12 "
Width W (Metric)	28.3 mm
Cable Tie Width Max. (Imperial)	0.18 "
Cable Tie Width Max. (Metric)	4.6 mm
Height H (Imperial)	0.23 "
Height H (Metric)	5.8 mm
Mounting Hole Diameter D (Imperial)	0.15 "
Mounting Hole Diameter D (Metric)	3.9 mm
Thickness of Adhesive TA (Imperial)	0.031 "
Mounting Hole Diameter D Max. (Metric)	3.9 mm
Mounting Hole Diameter D Min. (Metric)	3.9 mm
Thickness of Adhesive TA (Metric)	0.8 mm

Logistics and Packaging

Quantity Per	bag
Package Quantity (Metric)	500
Carton Quantity	4000

Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Adhesive Synthetic rubber with base of polyethylene foam

Adhesive Shortcut Synthetic rubber T50

Adhesive Operating Temperature -4°F to +122°F (-20°C to +50°C)

Flammability UL94 V2 (excluding adhesive)

Operating Temperature -40°F to +185°F (-40°C to +85°C)

ROHS Compliant Yes

UL Listed (US and Canada) No

UL Recognized (US and Canada) Yes