

MB5A10F4

Article Number: 151-00427

Adhesive Bases, .35" Max tie width, .19" Hole Dia., 1.49" Length/Width, PA66, White, 250/pkg



Download spec sheet

Base Data

Local Order Number MB5A10F4

Type MB5A

Color White (WH)

- Features and Benefits**
- For use with 18 and 30 pound cable ties to provide stability when securing bundles.
 - Secures with rubber based adhesive backing and/or two or four screws.
 - 4 way opening allows cable ties to be installed parallel or perpendicular to wire bundles.

Product Description HellermannTyton adhesive fastened mounting bases are used with 18 through 150 pound cable ties to provide stability when securing bundles. The mounts are installed using the adhesive backing and/or by securing two or four screws. The 4 way opening allows the cable ties to be inserted parallel or perpendicular to the wire bundles.

Short Description Adhesive Bases, .35" Max tie width, .19" Hole Dia., 1.49" Length/Width, PA66, White, 250/pkg

Product Dimensions

Length L (Imperial) 1.49 "

Length L (Metric) 37.7 mm

Fixation Method Screw Mounting and Adhesive

Width W (Imperial) 1.49 "

Width W (Metric) 37.7 mm

Cable Tie Width Max. (Imperial) 0.35 "

Cable Tie Width Max. (Metric) 8.9 mm

Height H (Imperial) 0.28 "

Height H (Metric) 7.1 mm

Mounting Hole Diameter D (Imperial) 0.19 "

Mounting Hole Diameter D (Metric) 4.8 mm

Mounting Hole Centers (Imperial) 1.0 "

Mounting Hole Diameter D Max. (Metric) 4.8 mm

Mounting Hole Diameter D Min. (Metric) 4.8 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 250

Carton Quantity 2000

Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability UL94 V2 (excluding adhesive)

Operating Temperature -40°F to +185°F (-40°C to +85°C)

ROHS Compliant Yes

UL Listed (US and Canada) No

UL Recognized (US and Canada) Yes