

Save with a BMP®41 Label Printer Starter Kit



BMP®41 Starter Kits

Catalog #	Description
BMP41-KIT-VD	BMP41 DataComm Starter Kit
BMP41-KIT-EL	BMP41 Electrical Starter Kit
BMP41-KIT-GI	BMP41 Facility ID Starter Kit

*Printer ships with BMP41 Rechargeable Battery Pack, MC1-1000-595-WT-BK cartridge, USB Cable, AC Adapter, Product CD, Brady Printer Drivers CD and Quick Start Guide.

BMP®41 DataComm Starter Kit Includes:

- 1 - BMP41 Label Maker Standard Package (BMP41-KIT)
- 1 - BMP41 Hard Case (BMP41-HC)
- 1 - B-427 1.0" White Label Roll (M-51-427)
- 1 - B-412 0.475" White Label Roll (MC-475-412)
- 1 - B-5951.0" Black on Yellow Label Roll (MC1-1000-595-YL-BK)
- 1 - B-5951.0" Black on White Label Roll (MC1-1000-595-WT-BK)

BMP®41 Electrical Starter Kit Includes:

- 1 - BMP41 Label Maker Standard Package (BMP41-KIT)
- 1 - BMP41 Hard Case (BMP41-HC)
- 1 - B-427 1.0" White Label Roll (M-143-427)
- 1 - B-498 1.0" White Label Roll (M-48-498)
- 1 - B-342 0.75" White Label Roll (M-187-075-342)
- 1 - B-595 1.0" Black on Orange Label Roll (MC1-1000-595-OR-BK)
- 1 - B-595 1.0" Black on White Label Roll (MC1-1000-595-WT-BK)

BMP®41 Facility ID Starter Kit Includes:

- 1 - BMP41 Label Maker Standard Package (BMP41-KIT)
- 1 - B-595 1.0" Black on Yellow Label Roll (MC1-1000-595-YL-BK)
- 1 - B-595 1.0" Red on White Label Roll (MC1-1000-595-WT-RD)
- 1 - B-595 1.0" White on Green Label Roll (MC1-1000-595-GN-WT)
- 1 - B-595 1.0" Black on White Label Roll (MC1-1000-595-WT-BK)
- 1 - B-483 1.0" White Label Roll (M-60-483)

Indoor / Outdoor Grade Facility & Safety Labels

This low-shrink, continuous vinyl material is pliable with an extremely aggressive adhesive that conforms to smooth or rough surfaces. Ideal for lean 5S labels, pipe markers, equipment and panel labels, and production area ID. Lasting up to 8-10 years outdoors, these labels offer excellent resistance to oils, detergents, dirt, grime and many solvents.

B-595 Indoor/Outdoor Vinyl Material - Permanent adhesive, very pliable, good for rough surfaces and outdoor use, wide range of colors. Temp. Range: -40°F to 248°F (-40°C to 120°C). UL recognized.



Figure 33



Fits Printer Models	Diagram	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Roll Length B Inch (mm)	Labels/Roll
B-595 – Indoor/Outdoor Vinyl Tape								
BMP41, 51, 53	Fig. 33	MC-500-595-WT-BK	B-595	Vinyl	BK on WT	0.500 (12.7)	25 ft. (7.6 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 33	MC-750-595-WT-BK	B-595	Vinyl	BK on WT	0.750 (19.1)	25 ft. (7.6 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 33	MC1-1000-595-WT-BK	B-595	Vinyl	BK on WT	1.000 (25.4)	25 ft. (7.6 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 33	MC-500-595-YL-BK	B-595	Vinyl	BK on YL	0.500 (12.7)	25 ft. (7.6 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 33	MC-750-595-YL-BK	B-595	Vinyl	BK on YL	0.750 (19.1)	25 ft. (7.6 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 33	MC1-1000-595-YL-BK	B-595	Vinyl	BK on YL	1.000 (25.4)	25 ft. (7.6 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 33	MC-500-595-OR-BK	B-595	Vinyl	BK on OR	0.500 (12.7)	25 ft. (7.6 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 33	MC-750-595-OR-BK	B-595	Vinyl	BK on OR	0.750 (19.1)	25 ft. (7.6 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 33	MC1-1000-595-OR-BK	B-595	Vinyl	BK on OR	1.000 (25.4)	25 ft. (7.6 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 33	MC-500-595-BL-WT	B-595	Vinyl	WT on BL	0.500 (12.7)	25 ft. (7.6 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 33	MC-750-595-BL-WT	B-595	Vinyl	WT on BL	0.750 (19.1)	25 ft. (7.6 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 33	MC1-1000-595-BL-WT	B-595	Vinyl	WT on BL	1.000 (25.4)	25 ft. (7.6 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 33	MC-500-595-RD-WT	B-595	Vinyl	WT on RD	0.500 (12.7)	25 ft. (7.6 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 33	MC-750-595-RD-WT	B-595	Vinyl	WT on RD	0.750 (19.1)	25 ft. (7.6 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 33	MC1-1000-595-RD-WT	B-595	Vinyl	WT on RD	1.000 (25.4)	25 ft. (7.6 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 33	MC-500-595-GN-WT	B-595	Vinyl	WT on GN	0.500 (12.7)	25 ft. (7.6 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 33	MC-750-595-GN-WT	B-595	Vinyl	WT on GN	0.750 (19.1)	25 ft. (7.6 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 33	MC1-1000-595-GN-WT	B-595	Vinyl	WT on GN	1.000 (25.4)	25 ft. (7.6 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 33	MC-500-595-WT-RD	B-595	Vinyl	RD on WT	0.500 (12.7)	25 ft. (7.6 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 33	MC-750-595-WT-RD	B-595	Vinyl	RD on WT	0.750 (19.1)	25 ft. (7.6 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 33	MC1-1000-595-WT-RD	B-595	Vinyl	RD on WT	1.000 (25.4)	25 ft. (7.6 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 33	MC-500-595-BK-WT	B-595	Vinyl	WT on BK	0.500 (12.7)	25 ft. (7.6 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 33	MC-750-595-BK-WT	B-595	Vinyl	WT on BK	0.750 (19.1)	25 ft. (7.6 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 33	MC1-1000-595-BK-WT	B-595	Vinyl	WT on BK	1.000 (25.4)	25 ft. (7.6 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 33	MC-500-595-CL-BK	B-595	Vinyl	BK on CL	0.500 (12.7)	25 ft. (7.6 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 33	MC-750-595-CL-BK	B-595	Vinyl	BK on CL	0.750 (19.1)	25 ft. (7.6 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 33	MC1-1000-595-CL-BK	B-595	Vinyl	BK on CL	1.000 (25.4)	20 ft. (7.6 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 33	MC-500-595-CL-WT	B-595	Vinyl	WT on CL	0.500 (12.7)	25 ft. (7.6 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 33	MC-750-595-CL-WT	B-595	Vinyl	WT on CL	0.750 (19.1)	25 ft. (7.6 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 33	MC1-1000-595-CL-WT	B-595	Vinyl	WT on CL	1.000 (25.4)	20 ft. (7.6 m)	1 roll (cont.)

