

RATINGS / APPROVALS

450°C – 300 Volts - UL 5128 / CSA AWM I A/B FTI

450°C – 600 Volts - UL 5107 / CSA AWM I A/B FTI

CONSTRUCTION

Conductors

24 AWG – 6 AWG (300 Volts)

24 AWG – 2 AWG (600 Volts)

Stranded nickel-coated copper - 27%

(Other conductor materials available)

Insulating System

Mica Tape

Outer Covering

Fiberglass braid with high temperature finish


Standard Color Coding

Natural and Solid Colors

Colored Tracers

CHARACTERISTICS

- Resists braid fray and push back.
- Withstands mechanical abuse.



Radix[™]

Radix Wire Company

26000 Lakeland Boulevard • Cleveland, OH 44132

Tel: 216 731-9191 • Fax: 216 731-7082

www.radix-wire.com

SPECIFICATIONS

MGT 450 HIGH-TEMPERATURE LEAD WIRE

MGT 450C/300V

Part No.	Awg. Size	# Strands	Outer Dia. inches	Outer Dia. mm	Wgt - lbs per 1000 ft.	Wgt - kg per km	UL	CSA
BDT24C007	24	7	0.072	1.83	3.80	5.65	5128	AWM I A/B FT I
BDT22C007	22	7	0.082	2.08	5.33	7.93	5128	AWM I A/B FT I
BDT20C010	20	10	0.087	2.21	6.50	9.67	5128	AWM I A/B FT I
BDT18C016	18	16	0.095	2.41	8.75	13.02	5128	AWM I A/B FT I
BDT16C026	16	26	0.107	2.72	12.37	18.40	5128	AWM I A/B FT I
BDT14C041	14	41	0.121	3.07	17.41	25.91	5128	AWM I A/B FT I
BDT12C065	12	65	0.140	3.56	25.53	37.99	5128	AWM I A/B FT I
BDT10C105	10	105	0.189	4.80	46.80	69.64	5128	AWM I A/B FT I

MGT 450C/600V

Part No.	Awg. Size	# Strands	Outer Dia. inches	Outer Dia. mm	Wgt - lbs per 1000 ft.	Wgt - kg per km	UL	CSA
BFT22C007	22	7	0.101	2.58	7.10	10.56	5107	AWM I A/B FT I
BFT20C010	20	10	0.106	2.69	8.35	12.42	5107	AWM I A/B FT I
BFT18C016	18	16	0.115	2.93	10.77	16.02	5107	AWM I A/B FT I
BFT16C026	16	26	0.127	3.23	14.55	21.65	5107	AWM I A/B FT I
BFT14C041	14	41	0.140	3.58	20.73	30.85	5107	AWM I A/B FT I
BFT12C065	12	65	0.160	4.06	29.37	43.71	5107	AWM I A/B FT I
BFT10C105	10	105	0.212	5.38	50.52	75.18	5107	AWM I A/B FT I
BFT08C133	8	133	0.262	6.65	74.29	110.56	5107	AWM I A/B FT I
BFT06C133	6	133	0.313	7.95	113.64	169.12	5107	AWM I A/B FT I
BFT04C133	4	133	0.368	9.35	167.42	249.16	5107	AWM I A/B FT I
BFT02C133	2	133	0.446	11.40	262.02	389.94	5107	AWM I A/B FT I

Standard conductor: Nickel Coated Copper - 27%
Consult factory for alternate conductor and stranding options.

® Registered trademark of Radix.

All dimensions listed above are nominal.

Compliance: UL Listed File No. E22244 • CSA Certified File No. LL13427 or LL80670

Information included in this catalog is intended as a guideline only. For applications that require tight tolerances, please contact the Radix factory for dimensional verification. Information herein is believed to be accurate as of publication date; however, if an error exists it is unintentional and Radix Wire Company, Inc. is not responsible for any claim traceable to such error.



Radix Wire Company
26000 Lakeland Boulevard • Cleveland, OH 44132
Tel: 216 731-9191 • Fax: 216 731-7082
www.radix-wire.com