

# MRK Series Gangable Rack Enclosures

FRAME ONLY		
10-32 Tapped Rails Part #	Server Mounting Rails Part #	Description
MRK-4431	MRK-4431PRO	44 RU 31" deep (29" useable) with solid rear door
MRK-4436	MRK-4436PRO	44 RU 36" deep (33.5" useable) with solid rear door
MRK-4442	MRK-4442PRO	44 RU 42" deep (39.5" useable) with solid rear door
MRK-2431	N/A	24 RU 31" deep (29" useable) with solid rear door
MRK-2436	N/A	24 RU 36" deep (33.5" useable) with solid rear door

ENCLOSURE OPTIONS					
Accessory Type	44 RU Part #	40 RU Part #	37 RU Part #	24 RU Part #	Description
front doors	FD-44	FD-40	FD-37	FD-24	solid front door
	LVFD-44	LVFD-40	LVFD-37	LVFD-24	perforated front door, 70% open area
	VFD-44	VFD-40	VFD-37	VFD-24	perforated front door
	PFD-44	PFD-40	PFD-37	PFD-24	smoked plexi-glass front door
	PVFD-44	N/A	N/A	N/A	plexi vented front door
rear doors	MW-VRD-44	N/A	N/A	N/A	partially vented rear door
	MW-LVRD-44	MW-LVRD-40	N/A	N/A	large perforated rear door
	MW-CLVRD-44	N/A	N/A	MW-CLVRD-24	split perforated rear door
	MW-CFRD-44	N/A	N/A	N/A	high CFM split rear door - 1320 CFM
side panels	SPN-44-312	SPN-40-312	SPN-37-312	SPN-24-312	side panels for 31" deep cabinet (sold in pairs)
	SPN-44-36	SPN-40-36	SPN-37-36	SPN-24-36	side panels for 36" deep cabinet (sold in pairs)
	SPN-44-423	SPN-40-423	SPN-37-423	N/A	side panels for 42" deep cabinet (sold in pairs)
leveling feet	LF	LF	LF	LF	leveling feet (set of four)
rackrails	MV-RR44	MV-RR44	MV-RR44	MV-RR24	additional pair of 10-32 mounting rails
	PROMRK-RR44	PROMRK-RR44	PROMRK-RR44	PROMRK-RR24	pair of server style mounting rails
caster bases	CBS-MRK-31	CBS-MRK-31	CBS-MRK-31	CBS-MRK-31	caster base option for 31" deep cabinet
	CBS-MRK-36	CBS-MRK-36	CBS-MRK-36	CBS-MRK-36	caster base option for 36" deep cabinet
	CBS-MRK-42	CBS-MRK-42	CBS-MRK-42	CBS-MRK-42	caster base option for 42" deep cabinet
top options	MW-ST	MW-ST	MW-ST	MW-ST	solid top panel
	MW-LVT	MW-LVT	MW-LVT	MW-LVT	large perforated top panel
	MW-10FT-550CFM	MW-10FT-550CFM	MW-10FT-550CFM	MW-10FT-550CFM	top panel configured with one 10" fan provides 550 CFM
	MW-6FT-660CFM	MW-6FT-660CFM	MW-6FT-660CFM	MW-6FT-660CFM	top panel configured with three 6" fans provide 660 CFM

RECOMMENDED ACCESSORIES		
Accessory Type	Part #	Description
power strip	PD-2415SC-NS	60" power strip, 24 outlet, 15 Amp with 10 ft. cord with 5-15P plug
	PD-2420SC-NS	60" power strip, 24 outlet, 20 Amp with 10 ft. cord with 5-20P plug
	PD-915R	1 RU rackmount power distribution unit (9) outlet, 15 Amp, 9 ft. cord
	PDT-2020C-NS	73" power strip, 20 outlet 20 Amp with 9 ft. cord with 5-20P plug
shelving	VSA-1626	< 1 RU 4-point mounting shelf, adjustable, 16-26 deep, 400 lbs. weight capacity
	VSA-2744	< 1 RU 4-point mounting shelf, adjustable, 27-44 deep, 400 lbs. weight capacity
hardware	U2V	2 RU front mount shelf 14.5" deep, 50 lb. weight capacity - vented
	HP	100 pieces additional mounting screws
	HP-6MM	100 pieces additional mounting screws
	CN6MM-100	100 pieces 6MM cage nuts
cable management	LACE-44-OWP	6-pack vertical lacing strips 44 RU

