


6 PAIR 20 AWG LEAD-FREE CABLE



SAFETY CERTIFICATION

UL Recognized: AWM Style 2464 80°C 300 Volts VW-1
CSA Certification: AWM II A/B 80°C 300 Volts FT1
ROHS Compliance: In Accordance to European Directive 2002/95/EC, Issue 13.2.2003

CONSTRUCTION

Pair Component

Conductor: 20 AWG 19/32 Tin Plated Copper, 0.038 Inch Diameter
Insulation: 0.010 Inches of XPbT, 0.058 Inch Diameter
Pair: 2 Insulated Conductors Twisted Together

Final Assembly

Core: Fibrillated Polypropylene Filler
Layer 1: 6 Pairs (#1-6) Cabled Around Core
Binder: Polyester Tape, 25% Overlap
Shield: 38 AWG Tin Plated Copper Braid, 75% Coverage
Jacket: 0.033 Inches of Super Flexible XPbT, Color – 4.6GY 9.07/0.6 Mist Gray
Diameter: 0.375 ± 0.010 Inches
Print Legend (Black Ink): “ AWM STYLE 2464 80°C 300V VW-1 MADISON CABLE CSA AWM II A/B 80°C 300V FT1 LEAD-FREE”

COLOR CODE

Pair #	Conductor #1	Conductor #2
1	White/Blue	Blue/White
2	White/Orange	Orange/White
3	White/Green	Green/White
4	White/Brown	Brown/White
5	White/Gray	Gray/White
6	Red/Blue	Blue/Red

ELECTRICAL CHARACTERISTICS

Conductor DC Resistance: 8.7 Ohms/1000 ft Nominal @ 20°C

Electronics

125 Goddard Memorial Drive • Worcester, MA 01603 USA
 Tel: (508) 752-2884 Toll-Free: (877) MADISON Fax: (508) 752-4230

REVISION HISTORY

Rev #	Date	By	Description
1	04/01/05	KA	Initial Release
2	04/06/05	KA	Added P/N

Spec Number:	101-2350
Part Number:	12RHLLF001
Customer:	
Customer #:	

Prepared By:	K. Arsenault	Reviewed By:	H. Abusamra	N. Allen	Page 1 of 1
---------------------	--------------	---------------------	-------------	----------	-----------------------