

Use this table to find the adhesive compatibility for your preferred material.

| Material Combinations | Material | | | |
|---|---------------------------|---------------------------------------|---------------------------------------|---|
| | G | B7 | B8 | H |
| Material Description | Fluid resistant elastomer | Semi -rigid flame retarded polyolefin | Semi -rigid flame retarded polyolefin | Flexible limited fire hazard polyolefin |
| Shape | | | | |
| Minimum Shrink Temperature °C | +135 | +135 | +135 | +135 |
| Operating Temperature Range °C | -75 to +150 | -55 to +135 | -55 to +100 | -55 to +105 |
| Shelf Life | 5 years | 5 years | 5 years | 5 years |
| Helashrink 100 Series | yes | yes | no | yes |
| Helashrink 1100 Series | yes | yes | no | yes |
| Helashrink 200 Series | yes | yes | no | yes |
| Helashrink 300 Series | yes | yes | no | yes |
| Helashrink 400 Series | yes | yes | no | yes |
| Helashrink 1200 Series | yes | yes | no | yes |
| Helashrink 1300 Series | yes | yes | no | yes |
| Low Profile Shapes (Series 313, 412, 492, 573) | no | no | no | no |
| Helashrink 1600 Series | no | no | yes | no |
| Helashrink In Line Series, low voltage | no | no | yes | no |
| Adhesive Compatibility | WM250 | WM250 | WM250 | WM250 |
| | W8 | W8 | W8 | W8 |
| | W24 | W24 | | W24 |
| | V9500 | V9500 | | W21 |
| | HMT200A | HMT200A | | |