

HellermannTyton Shapes for use with circular MIL Specification Connectors MS 5015 AB

Connector Shell Size	Knurl Dia (mm)	Orientation		Cable Dia (mm)	
		Straight	90°	Min	Max
10 SL*	15.7	153-42	1152-4/1106-4*	4.2	7.7
14 S	19.3	154-42/106-4	1154-4/1107-4	7.2	10.6
16 S	24.1	155-42/101-4	1155-4/1104-4	8.4	13.5
16	24.1	155-42/101-4	1155-4/1104-4	8.4	13.5
18	24.1	155-42/101-4	1155-4/1104-4	8.4	14.6
20	29.8	156-42/102-4	1156-4/1103-4	10.2	18.7
22	29.8	156-42/102-4	1156-4/1103-4	10.2	20.8
24	38.0	157-43/103-4	1157-4/1101-4	12.0	24.6
28	38.0	157-43/103-4	1157-4/1101-4	12.0	27.0
32	48.0	158-43/107-4	1158-4/1105-4	19.2	33.3
36	48.0	158-43/107-4	1158-4/1105-4	19.2	38.5

* Note: Shell 10 SL for 90° moulded part min cable diameter 6.6 mm

HellermannTyton Shapes for use with MIL-C-26482-I/II and 38999/Series I, II, III, IV

Connector Shell Size	Knurl Dia (mm)	Orientation		Cable Dia (mm)	
		Straight	90°	Min	Max
8/9	13.0	152-42/105-4	1152-4/1106-4	7.2	7.0
10/11	15.0	152-42/105-4	1152-4/1106-4	7.2	10.0
10/12	15.0/19.0	153-42/NA	-	7.2	10.0/13.5
12/13	19.0	154-42/106-4	1154-4/1107-4	7.2	13.5
14/15	21.0	155-42/101-4	1155-4/1104-4	8.4	16.5
16/17	24.0	155-42/101-4	1155-4/1104-4	8.4	19.5
18/19	26.5	156-42/102-4	1156-4/1103-4	10.2	22.0
20/21	30.5	156-42/102-4	1156-4/1103-4	10.2	25.0
22/23	34.0	157-43/103-4	1157-4/1101-4	12.0	28.5
24/25	36.0	157-43/103-4	1157-4/1101-4	12.0	31.0