



Round

REV	DATE	MODIFICATION	DRAWN
1	2013/09/05		

SPECIFICATIONS

1. ELECTRICAL:
 UL APPLICATIONS: 250 VOLTS AC MAX., AT 2 AMPS.
 DIELECTRIC WITHSTANDING VOLTAGE: 500 VOLTS AC.
 INSULATION RESISTANCE: 100M Ω.
 HUMIDIFICATION RESISTANCE: 20H @ MAX. AFTER ENVIRONMENTAL TESTING.

2. MECHANICAL:
 CABLE TO PLUG TENSILE STRENGTH: 19.6N/PCS MIN.
 DURABILITY: 200 MATING CYCLES.
 3. MATERIAL & FINISH:
 HOUSING: POLYCARBONATE, UL 94V-0 OR UL 94V-2.
 COLOR: TRANSPARENT OR OTHER COLOR ARE AVAILABLE.
 CONTACTS: COPPER ALLOY.
 CONDUCTOR: SOLID WIRE, 24AWG, 26 AWG.
 GOLD PLATING: 50"

BLADE:	B
Drawing	
Mark	

		Quest Technology International, Inc. 11200 NW 138th St. Medley, FL 33178	
DIMENSION IN mm (Inch)	TOLERANCE UNLESS OTHERWISE SPECIFIED	材料名	图号
X±0.20	X°±5°	PC	NMP-8215
.XX±0.10	.XX°±2°	名称	图名
审批	校对	Catlyli	比例
核准	检查	比例	2/1
Approval	Checked	图名	张数
		Catlyli	1/1
		图名	更改
		比例	A
		图号	

1 2 3 4 5 6 7

ST-DR-009A