UL 2571 | Irrigation Feeder, Control and Signal Cables

Harsh Duty. Dependable.

Remote applications demand reliable performance in extreme environments. Engineered to withstand chemicals and UV, our flame resistant, ultra-reliable products are designed and built to last! Ideally suited to supply signal, power and control to water management systems including central pivot, linear and lateral irrigation machines.

	TFN, TFFN	THWN-2
FEATURES		
Signal	✓	✓
Control	✓	✓
Power	✓	✓
ATTRIBUTES		
Low-Temperature Rating	-25°C	-25℃
High-Temperature Rating	60°C or 75°C	60°C or 75°C
Cold Bend	-25°C	-25℃
Flame Resistant	VW-1	VW-1
Direct Burial	✓ *	√ *
Wet Location Use	✓	✓
Chemical Resistant	✓	✓
Sunlight/UV Resistant	✓	✓
FLEXIBILITY		
Torsional Flex	*	*
Rolling Flex	*	*
Variable Flex	*	*
Bend Flex	*	*
Continuous Flex	*	*
STANDARDS, AGENCY AND ENVIRONMENTAL COMPLIANCE		
UL	\checkmark	✓
ANSI	✓	✓
CE	✓	✓
NEC [®]	✓	✓
NFPA 70	✓	✓
RoHS2	✓	✓
REACH	✓	✓

* Requires inner jacket over core assembly

got rodents?

Anti-rodent additives are environmentally-friendly, patented bio-active ingredients that effectively repel rodents and help you avoid:

- Safety issues
- Equipment damage
- Productivity downtime
- Loss of revenue

For more information, see page 32



STANDARDS, AGENCY AND ENVIRONMENTAL COMPLIANCE:

















- Not Applicable
- ✓ Featured
- ★ Cost Competitive Custom Options Available