

SINGLE



NWI EXPRESS
5 Days Design to Deliver

STYLE # 1277 - 1331

Style Number	Temperature °C	AWG and/or kcmil	Voltage V	Material
1277	60, 80	4/0 - 500	600	PVC
1278	60, 80	4 - 4/0	600	PVC
1279	60, 80	7 - 2	600	PVC
1280	80	18 - 8	600	PVC
1282	80	26 - 16	300	PE / Shield / PVC
1287	60	26 - 16	600	PE / Shield / PVC
1288	80	26 - 16	300	PE / Shield / Lacquered fibrous braid* / PVC
1289	60	26 - 16	600	PE / Shield / PVC
1291	80	29	300	PE / Shield (closely woven braid) / PVC
1293	105	30 - 20	not specified	FEP / Nylon
1294	80	30 - 20	not specified	FEP / Nylon
1295	80	26 - 16	300	PE / Shield / PVC
1297	80	26 - 16	300	PE / Shield / PVC
1298	80	26 - 16, 27	300	PE / Shield / PVC
1299	80	26 - 20	300	FRPE / FRPE tube / Shield / Nylon / Braid* / PVC
1300	80	26	600	PE / Shield* / PVC
1310	60	18 - 10	600	PVC
1311	80	18 - 10	600	PVC
1316	90, 105	26 - 12	600	PVC / Nylon
1317	90, 105	10	600	PVC / Nylon
1318	90, 105	8 - 6	600	PVC / Nylon
1319	90, 105	4 - 2	600	PVC / Nylon
1320	90, 105	1 - 4/0	600	PVC / Nylon
1321	90, 105	250 - 1000	600	PVC / Nylon
1322	90	14 - 10	600	PVC
1323	60, 80	14 - 10	600	PVC
1324	80	30 - 16	300	PE / Shield* / PVC
1325	80	26 - 16	600	PE / Shield / PVC
1326	80	26 - 16	600 insulation, 300 jacket	PE / Shield / PVC
1329	105	14 - 10	600	PVC
1330	200	30 - 4/0	600	FEP / Glass braid, FEP*
1331	150	30 - 4/0	600	FEP / Glass braid, FEP*

* Optional UL Style constructions available

STYLE # 1332 - 1383

Style Number	Temperature °C	AWG and/or kcmil	Voltage V	Material
1332	200	30 - 10	300	FEP / Glass braid, FEP*
1333	150	30 - 10	300	FEP / Glass braid, FEP*
1334	60	26 - 16	600	PE / Shield / Lacquered rayon braid / PVC
1335	90	26 - 10	600	PVC
1336	90	8	600	PVC
1337	90	6 - 2	600	PVC
1338	90	1 - 4/0	600	PVC
1339	90	4/0 - 500	600	PVC
1340	60, 90	500 - 1000	600	PVC
1342	105	14 - 10	600	PVC
1343	105	18 - 10	600	PVC
1344	105	18 - 8	600	PVC
1345	105	26 - 9	600	PVC
1346	105	8 - 2	600	PVC
1347	80	26 - 16	300	PVC / Shield / PVC
1348	60	26 - 16	300	PE / Shield / PVC
1349	80	26 - 16	300	PVC / Shield / PVC
1350	80	26 - 16	600	PE / PVC
1354	60, 80	44 minimum	30	Solid, cellular optional / Solid inner, middle shield* / Outer shield
1355	200	32 - 20	not specified	FEP / Nylon
1365	60	30 - 16	300	FRPE / PVC* / Shield* / PVC / Shield* / PVC*
1366	90	26 - 9	600	PVC / PVC
1369	90	Resistance wire (size varies dependant on wattage)	250	PVC
1371	105	36 - 6	not specified	FEP, PTFE extruded / FEP or PTFE extruded, PFA
1380	60	29 - 20	300	FRPE / FRPE tube / Shield* / PVC
1381	60, 80	29 - 20	600	PE / FRPE tube / Shield* / PVC
1382	80	29 - 20	300	PE / FRPE tube / Shield* / PVC
1383	90	18 - 10	600	PVC

* Optional UL Style constructions available