

SINGLE



NWI EXPRESS
5 Days Design to Deliver

STYLE # 1644 - 1864

Style Number	Temperature °C	AWG and/or kcmil	Voltage V	Material
1644	150	30 - 4/0	600	Extruded ETFE
1645	105	Flat wire, 0.400 - 1.500 inches width	90	ETFE
1646	105	26 - 16 flat	not specified	ETFE
1649	105	15 - 5 flat 0.400 - 1.500 inches width	90	ETFE
1670	150	32 - 14	not specified	ETFE
1671	150	32 - 10	300	ETFE
1686	105	32 - 20	not specified	ECTFE
1687	105	32 - 20	not specified	ECTFE
1688	105	32 - 20	not specified	ECTFE
1689	105	30 - 16	not specified	ECTFE
1692	80, 90, 105	42 minimum	30	PVC
1704	150	32 - 10	300	ECTFE
1705	150	30 - 4/0	600	ETFE
1708	200	32 - 20	not specified	PFA
1726	250	32 - 4/0	300	MFA, PFA
1729	80	50 - 16	300	PVC / Nylon*
1730	90	32 - 16	300	PVC / Nylon*
1731	105	50 - 16	300	PVC / Nylon*
1766	80	42 minimum	30	Solid, cellular FEP
1813	200	30 - 10	3000	FEP
1814	150	36 - 20	150	ETFE
1827	150	32 - 10	125	Extruded ETFE
1828	150	32 - 10	300	ETFE
1829	150	32 - 10	600	ETFE
1831	105	24 - 18	150	ETFE / PVC*
1837	60	40 minimum	30	Solid, cellular FEP / Shield* / FEP
1841	105	26 - 12	600	PVC / Nylon
1842	90	26 - 9	600	PVC / Nylon
1847	105	40 minimum	30	FEP
1862	125	32 - 16	150	ETFE
1863	125	32 - 10	300	ETFE
1864	125	30 - 4/0	600	ETFE

* Optional UL Style constructions available

STYLE # 1873 - 10050

Style Number	Temperature °C	AWG and/or kcmil	Voltage V	Material
1873	105	36 - 18	300	PVC
1886	150	30 - 10	300	FEP
1887	150	30 - 4/0	600	FEP
1900	200	30 - 10	300	FEP
1901	200	30 - 4/0	600	FEP
1903	60	32 - 14	300	PE, FRPE
1905	105	32 - 20	30	ETFE
1920	60	23 - 10	600	Solid of cellular PE, FRPE
1921	80	32 - 4/0	300	PE, FRPE
1922	80	32 - 10	600	PE, FRPE
1933	250	36 - 20	not specified	PFA
1947	105	26 - 20	600	PVC / Nylon
1970	60, 80	32 - 20	300	Cellular FEP
1973	60, 80	36 - 16	300	PE, FRPE
1976	80	36 - 18	300	SRPVC
1984	105	36 - 16	300	PVC
1988	105	32 - 10	150	ETFE
1989	105	32 - 10	300	ETFE
1990	105	30 - 4/0	600	ETFE
1999	150	36 - 10	300	Solid, cellular FEP / Shield* / FEP
10002	105	32 - 16	300	SRPVC
10009	150	36 minimum	300	Solid, cellular FEP / Shield* / FEP
10027	105	36 - 18	300	PVC
10030	250	30 - 10	300	PFA / Felted impregnated glass
10032	250	30 - 10	600	PFA / Felted impregnated glass
10033	105	Resistance wire (size varies dependent on wattage)	600	ETFE / Nylon* / ETFE / PVC*
10042	80	32 - 2	300	TPES
10043	80	40 minimum	30	PVC / Shield* / Nylon*
10045	150	36 - 14	not specified	FEP
10048	200	30 - 10	1000	FEP
10050	150	30 - 4/0	600	FEP

* Optional UL Style constructions available

Products

AGENCY STANDARDS