

MULTI



NWI EXPRESS
5 Days Design to Deliver

STYLE # 2215 - 2262

Style Number	Temperature °C	AWG and/or kcmil	Voltage V	Material
2215	60	22 - 16	300	PVC (Type SPT-1 cord)
2216	60	22 - 16	300	PVC (Type SPT-1 cord)
2217	60	22 - 16	300	PVC (Type SPT-1 cord)
2218	60	22 - 16	300	PVC (Type SPT-1 cord)
2219	60	22 - 16	300	PVC (Type SPT-1 cord)
2220	60	22 - 16	300	PVC (Type SPT-1 cord)
2221	60	22 - 16	300	PVC (Type SPT-1 cord)
2222	60	22 - 16	300	PVC (Type SPT-1 cord)
2223	60	22 - 16	300	PVC (Type SPT-1 cord)
2224	60	22 - 16	300	PVC (Type SPT-1 cord)
2225	80	20, 18, 16	300	PVC (Type SPT-2 cord)
2226	90	20, 18, 16	300	PVC (Type SPT-2 cord)
2227	105	20, 18, 16	300	PVC (Type SPT-2 cord)
2228	80	20, 18, 16	300	PVC (Type SPT-2 cord)
2229	90	18, 16	300	PVC (Type SPT-3 cord)
2230	105	18, 16	300	PVC (Type SPT-3 cord)
2231	80	14, 12, 10	600	PVC (Type SPT-3 cord)
2232	90	14, 12, 10	600	PVC (Type SPT-3 cord)
2233	105	14, 12, 10	600	PVC (Type SPT-3 cord)
2234	80	18, 16	300	PVC (Type SPT-2 cord)
2235	90	18, 16	300	PVC (Type SPT-2 cord)
2236	105	18, 16	300	PVC (Type SPT-2 cord)
2237	80	18, 16	600	PVC (Type SPT-3 cord)
2238	90	18, 16	600	PVC (Type SPT-3 cord)
2240	60	20 and 18	300	PVC / PVC (Type SJT cord)
2246	60	20	300	PVC / PVC (Type SJT cord)
2247	80	26 - 16	300	PVC / PVC (Type SJT cord)
2248	60	20	300	PVC / PVC (Type SJT cord)
2249	80	26 - 16	300	PVC / PVC (Type SJT cord)
2250	60	20	300	PVC / PVC (Type SJT cord)
2251	80	26 - 16	300	PVC / PVC (Type SJT cord)
2252	80	18 - 16	300	PVC / PVC (Type SVT cord)
2253	80	18 - 16	300	PVC / PVC (Type SVT cord)
2254	80	18 - 16	300	PVC / PVC (Type SVT cord)
2255	80	18 - 16	300	PVC / PVC (Type SVT cord)
2257	60	18 - 10	300	PVC / PVC (Type SJT cord)
2262	60	26 - 16	600 insulation, 300 jacket	PE / Shield / PVC

* Optional UL Style constructions available

STYLE # 2263 - 2385

Style Number	Temperature °C	AWG and/or kcmil	Voltage V	Material
2263	60	26 - 16	600 insulation, 300 jacket	PE / Shield / PVC
2264	60	26 - 16	600 insulation, 300 jacket	PE / Shield / PVC
2265	80	26 - 16	300	PVC / Shield* / PVC
2266	80	26 - 16	300	PVC / Shield* / Jacket
2267	80	26 - 16	300	PVC / Shield / PVC
2268	80	26 - 16	600 insulation, 300 jacket	PVC / Shield / PVC
2269	80	26 - 16	600 insulation, 300 jacket	PVC / Shield / Braid* / PVC
2270	80	26 - 16	600 insulation, 300 jacket	PVC / Shield / PVC
2310	80	22 - 16	600	PVC / Shield / PVC
2311	60	26 - 16	600	FRPE, PE / Shield / PVC
2319	90	26 - 16	600	PVC / PVC
2321	80	22	600	PVC / Shield / PVC
2343	80	30 minimum	not specified	Shield* / PVC / PVC
2344	80	30 minimum	not specified	Shield* / PVC / PVC
2345	80	30 minimum	not specified	PVC* / Shield* / PVC
2346	80	30 minimum	not specified	Shield* / PVC / PVC
2350	80	26 - 16	600 insulation, 300 jacket	PE / Shield / PVC
2352	80	26 - 16	600 insulation, 300 jacket	PE / Shield / PVC
2353	80	26 - 16	600 insulation, 300 jacket	PE / Shield / PVC
2355	80	26 - 16	600	PE / Shield / PVC
2356	105	20	300	PVC / PVC
2373	80	26 - 16	300	FRPE, PE / Lacquered glass, rayon* / Shield / PVC
2376	105	26 - 16	300	PVC / Shield* / PVC
2377	60	22 - 16	300	PVC / PVC (Type SJT cord)
2378	60	22 - 16	300	PVC / PVC (Type SJT cord)
2379	60	22 - 16	300	PVC / PVC (Type SJT cord)
2380	60	22 - 16	300	PVC / PVC (Type SJT cord)
2381	60	22 - 16	300	PVC / PVC (Type SJT cord)
2382	60	22 - 16	300	PVC / PVC (Type SJT cord)
2383	60	22 - 16	300	PVC / PVC (Type SJT cord)
2384	60	40 - 10	30	Shield* / PVC / PVC
2385	60	40 - 10	30	Shield* / PVC* / PVC

* Optional UL Style constructions available

Products

AGENCY STANDARDS