

# UL 758 | Appliance Wiring Material

## UL Recognized AWM Style

### THERMOPLASTIC INSULATION (CONTINUED)

#### MULTI CONDUCTOR



STYLE # 2386 - 2560

Style Number	Temperature °C	AWG and/or kcmil	Voltage V	Material
2386	60	40 - 10	30	Shield* / PVC* / PVC
2387	60	40 - 10	30	Shield* / PVC* / PVC
2388	60	40 - 10	30	Shield* / PVC* / PVC
2439	80	26 - 16	600	PE / Shield / PVC
2447	60	20 - 18	300	PVC / PVC
2448	60, 80	40 minimum	30	Shield* / PVC* / PVC* / PVC
2449	105	26 - 16	300	PVC / PVC (Type SJT cord)
2450	105	26 - 16	300	PVC / PVC (Type SVT cord)
2461	80	26 - 16	300	Shield* / PVC* / PVC
2463	80	40 minimum	600	Shield* / PVC* / PVC
2464	80	-	300	Shield* / PVC* / Braid* / PVC
2468	80	32 - 16	300	PVC / Shield* / PVC*
2481	105	26 - 16	600 insulation, 300 jacket	PVC / Shield / PVC
2482	105	26 - 16	300, 600	PVC / Shield / PVC
2490	60	36 minimum	not specified	Shield* / PVC, PTFE, Etc. / PVC
2493	60	30 - 16	not specified	Shield* / PVC* / PVC
2501	105	40 minimum	600	PVC* / Shield* / PVC
2502	80	40 minimum	30	Shield* / PVC* / PVC
2516	105	40 minimum	600	Shield* / PVC* / PVC
2517	105	40 minimum	300	Shield* / PVC* / Braid* / PVC
2532	80	40 minimum	30	Shield* / PVC* / PVC
2535	80	40 minimum	30	Shield* / PVC* / PVC
2549	90	40 - 16	300	Shield* / PVC* / PVC
2550	90	40 minimum	600	Shield* / PVC* / PVC
2551	105	40 minimum	30	PVC
2552	60	40 minimum	30	PE, cellular PE, XLPE, cellular XLPE, FRPE, cellular FRPE, XLFRPE, cellular XLFRPE, PP, cellular PP, XLPP, cellular XLPP / Shield* / PVC, Nylon, TPES, PVDF, Lacquered braid* / PE, cellular PE, XLPE, cellular XLPE, FRPE, cellular FRPE, XLFRPE, cellular XLFRPE, PP, cellular PP, XLPP, cellular XLPP* / PVC / Shield* / PVC*
2560	60	-	30	Shield* / PVC

\* Optional UL Style constructions available

STYLE # 2564 - 2934

Style Number	Temperature °C	AWG and/or kcmil	Voltage V	Material
2564	75	22 and 18	125	PVC / PVC
2570	80	40 minimum	600, 1000	Shield* / PVC / PVC* / PVC
2571	80	40 minimum	not specified	Shield* / PVC* / PVC
2574	105	40 minimum	30	Shield* / PVC* / PVC
2576	80	36 - 9	150	Shield* / PVC* / PVC
2582	60	30 - 16	150	FRPE, PE / Shield* / PVC* / PVC
2584	80	40 - 9	125	Shield* / PVC* / PVC
2586	105	40 minimum	600, 1000	Shield* / PVC* / PVC
2587	90	40 minimum	600	Shield* / PVC* / PVC
2598	60	-	300	Shield* / PVC* / PVC
2610	80	32 - 16	300	Style 1007 / PVC
2614	105	40 minimum	30	Shield* / PVC* / PVC
2626	80	-	30	Shield* / PVC* / PVC
2631	90	40 minimum	not specified	Shield* / PVC* / PVC
2661	80, 90, 105	40 - 6	300	PVC* / Shield* / PVC
2668	60	40 minimum	30	Shield* / PVC* / PVC
2704	60	40 minimum	30	Shield* / PVC* / PVC
2709	60	40 minimum	30	Shield* / PVC* / PVC
2722	105	26 - 15	300	PVC (Type SPT cord)
2747	150	-	300	Shield* / FEP
2748	150	-	600	Shield* / FEP
2749	200	-	300	Shield* / FEP
2750	200	-	600	Shield* / FEP
2778	60	30 - 16	150	Shield* / PVC* / PVC
2789	60	-	30	Shield* / PVC, PTFE, PFA, FEP, ETFE* / PVC, PTFE, PFA, FEP, ETFE* / PVC
2839	90	-	600	Shield* / PVC* / PVC
2841	80	40 minimum	30	Shield* / PVC
2842	80	40 minimum	30	Shield* / PVC
2876	80	40 minimum	not specified	Shield* / PVC
2894	150	-	300	Shield* / FEP
2895	200	-	300	Shield* / FEP
2919	80	40 minimum	30	Shield* / PVC* / Braid* / PVC
2920	60	40 - 10	30	Shield* / PVC
2934	80	-	150	Shield* / PVC* / PVC

\* Optional UL Style constructions available