

# MULTI



**NWI EXPRESS**  
5 Days Design to Deliver

## STYLE # 2935 - 20379

Style Number	Temperature °C	AWG and/or kcmil	Voltage V	Material
2935	80	–	300	Shield* / PVC* / PVC
2960	60	32 minimum	30	PP, PE / PVC* / Shield* / PVC
2961	80	–	150	Shield* / PVC* / PVC
2969	80	40 minimum	30	Shield* / PVC* / PVC
2983	150	–	150	Shield* / FEP
2990	80	40 minimum	30	Shield* / PVC* / PVC
2991	105	40 minimum	30	Shield* / PVC* / PVC
2992	105	40 minimum	30	Shield* / PVC* / PVC
2993	60	40 minimum	30	Shield* / PVC* / PVC
20030	60	18 - 2	600	FEP, PE, PVC / PVC (Type STO cord)
20031	75	18 - 2	600	FEP, PE, PVC / PVC (Type STO cord)
20032	90	18 - 2	600	FEP, PE, PVC / PVC (Type STO cord)
20033	105	18 - 2	600	FEP, PE, PVC / PVC (Type STO cord)
20224	200, 250	–	300	Shield* / PFA
20225	200, 250	–	600	Shield* / PFA
20229	150	–	300	Shield* / FEP
20230	150	–	600	Shield* / FEP
20233	80	36 minimum	300	Shield* / PUR* / Braid* / PUR
20234	80	–	600, 1000	Shield* / PUR* / Braid* / PUR
20235	80	36 minimum	not specified	Shield* / PVC* / PUR
20236	80	36 minimum	30	Shield* / PVC* / PUR
20248	80	–	300	Shield* / FEP
20249	80	–	30	FEP
20262	200	30 - 10	300	Style 1332 / Shield* / FEP
20265	80	–	30	Shield* / PVC
20266	80	–	150	Shield* / PVC
20267	80	–	300	Shield* / PVC
20308	150	30 - 10	300	Style 1333 / Shield* / FEP
20315	125	28 - 10	600	TPE (Type SPE cord)
20327	105	36 minimum	300	Shield* / TPE
20328	105	36 minimum	600	Shield* / TPE
20368	200	–	300	Shield* / FEP
20379	80	50 minimum	30	Shield* / PVC* / PVC

\* Optional UL Style constructions available

## STYLE # 20387 - 21840

Style Number	Temperature °C	AWG and/or kcmil	Voltage V	Material
20387	105	–	300	Shield* / PVC
20404	60, 75, 80, 90, 105	18 - 10	300	PVC (Type SPT-3 cord)
20549	80	32 minimum	300	PVC* / Shield* / PUR
20604	200	–	300	Shield* / FEP* / FEP
20626	80, 90	–	30, 150, 300, 600	Shield* / TPE* / Braid* / TPE
20710	200	–	600	Shield* / FEP
20711	200	–	300	Shield* / FEP
20712	150	–	600	Shield* / FEP
20713	150	–	300	Shield* / FEP
20787	60, 75, 80, 90, 105	18 - 16	300	PVC (Type SPT-2 cord)
20810	105	40 - 10	30	FEP / FEP
20838	105	–	300	Braid* / PVC / PVC
20883	60, 80, 90, 105	–	150, 300, 600	Shield* / PVC
20920	200	–	150	Shield* / FEP
20947	80	–	30	Shield* / PVC* / PVC* / PVC
21002	105	–	300, 600	Shield* / TPE* / Braid* / TPE
21022	60, 75, 90, 105	26 - 16	300	PVC (Type SPT-2 cord)
21048	60, 75, 90, 105	18 - 10	300	(Type SPT-2, SVT, SJT cord) / Braid*
21103	105	40 minimum	30	Shield* / PVC* / PVC
21191	125	50 - 2000	30	Shield* / TPE* / TPE
21192	125	50 - 2000	150	Shield* / TPE* / TPE
21193	125	50 - 2000	300	Shield* / TPE* / TPE
21194	125	50 - 2000	600	Shield* / TPE* / TPE
21198	80	32 minimum	300	Shield* / PUR* / PUR
21397	75	50 - 1	300	Shield* / Binder* / PVC
21840	105	–	1000	TPE* / TPE

\* Optional UL Style constructions available

Products

AGENCY STANDARDS