UL 62 | CSA 49 | cUL 49 | Flexible Cords and Cables

Extensive Rugged Wire, Cable and Retractiles Options.

Global markets are easily accessible with our internationally recognized standards. Our versatile offering features the harmonized standards of the United States, Canada and Mexico. This widely recognized standard complies with all three requirements after minor adjustments. Leveraging advanced materials and manufacturing technology, custom solutions are engineered for rigorous electrical, mechanical, ergonomic, aesthetic and extreme environmental conditions. Our design experts will navigate you through the complexities of harmonized standards to achieve a custom solution that meets your requirements.

	Service Parallel Thermoplastic			Non-Integral Service Parallel Thermoplastic		Service Parallel Elastomer		
	SPT-1	SPT-2	SPT-3	NISPT-1	NISPT-2	SPE-1	SPE-2	SPE-3
FEATURES								
Power	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
ATTRIBUTES								
Low-Temperature Rating	≤ -20°C	≤ -20°C	≤ -20°C	≤ -20°C	≤ -20°C	≤ -20°C	≤ -20°C	≤ -20°C
High-Temperature Rating	105°C	105°C	105°C	105°C	105°C	105°C	105°C	105°C
Cold Bend	≤ -20°C	≤ -20°C	≤ -20°C	≤ -20°C	≤ -20°C	≤ -20°C	≤ -20°C	≤ -20°C
Flame Resistant	VW-1, FT2	VW-1, FT2	VW-1, FT2	VW-1, FT2	VW-1, FT2	VW-1, FT2	VW-1, FT2	VW-1, FT2
Wet Location Use	-	-	-	-	-	-	-	-
Oil Resistant	-	_	_	_	-	-	-	-
Sunlight/UV Resistant	-	-	-	-	-	-	-	-
Weld Flash Resistant	-	_	_	_	-	-	-	-
Weld Slag Resistant	-	-	-	-	-	-	-	-
STANDARDS, AGENCY AND ENVIRONMENTAL COMPLIANCE								
UL	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
ANSI	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
CSA	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
cUL	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
NEC®	Article 400	Article 400	Article 400	Article 400	Article 400	Article 400	Article 400	Article 400
MSHA	-	-	-	-	-	-	-	-
RoHS2	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
REACH	*	*	*	*	*	*	*	*

REACH

* Low-Temperature Rating must have a "W" rating to call the TPE -50°C. National differences for US, Canada & Mexico exist, please contact our experienced designers for assistance.

STANDARDS, AGENCY AND ENVIRONMENTAL COMPLIANCE:

