

UL 1063 | Machine-Tool Wires and Cables

High Flex Options Make Installation Easy.

Manufactured in the USA for over 40 years, our cost competitive, easy to install MTW is oil, chemical and water resistant. UL listed, our MTW is flame resistant and ideally suited for wet location use, wiring new facilities or rewiring existing plants and more.

	Single Conductors		2 or More Conductors	
FEATURES				
Signal	✓	✓	✓	✓
Control	✓	✓	✓	✓
Instrumentation	✓	✓	✓	✓
Power	✓	✓	✓	✓
ATTRIBUTES				
Low-Temperature Rating	-20°C	-20°C	-20°C	-20°C
High-Temperature Rating	90°C	90°C	90°C	90°C
Flame Resistant	VW-1, UL 1581 Section 1060, FT2	VW-1, UL 1581 Section 1060, FT2	VW-1, UL 1581 Section 1060, FT2	VW-1, UL 1581 Section 1060, FT2
Wet Location Use	✓	✓	✓	✓
Oil Resistant	✓	✓	✓	✓
Chemical Resistant	✓	✓	✓	✓
FLEXIBILITY				
Torsional Flex	★	★	★	★
Rolling Flex	★	★	★	★
Variable Flex	★	★	★	★
Bend Flex	★	★	★	★
Continuous Flex	★	★	★	★
STANDARDS, AGENCY AND ENVIRONMENTAL COMPLIANCE				
UL	✓	✓	✓	✓
ANSI	✓	✓	✓	✓
CE	✓	✓	✓	✓
NEC®	✓	✓	✓	✓
NFPA 70	✓	✓	✓	✓
NFPA 79	✓	✓	✓	✓
RoHS2	✓	✓	✓	✓
REACH	✓	✓	✓	✓

STANDARDS, AGENCY AND ENVIRONMENTAL COMPLIANCE:



KEY:

- Not Applicable
- ✓ Featured
- ★ Cost Competitive Custom Options Available