

# UL 44 | Thermoset-Insulated Wires and Cable

## Cost Savings, Easy Installation with Extreme Flex Options.

Cross-linked and flame resistant, our high heat, cold temperature, UV, and water resistant UL 44 listed products are principally suited for factory settings. Widely recognized and versatile. For easy installation, select from a range of extreme flex options, torsional, rolling, variable, bend, and continuous.

	XHH, XHHW, XHHW-2	RHH, RHW, RHW-2
<b>FEATURES</b>		
Power	✓	✓
<b>ATTRIBUTES</b>		
Low-Temperature Rating	≤-25°C	≤-25°C
High-Temperature Rating	≥ 90°C	≥ 90°C
Cold Bend	≤-25°C	≤-25°C
Cold Impact	★	★
Flame Resistant	VW-1, FT1	VW-1, FT1
Wet Location Use	✓	✓
Oil Resistant	PRI and PRII	PRI and PRII
<b>FLEXIBILITY</b>		
Torsional Flex	★	★
Rolling Flex	★	★
Variable Flex	★	★
Bend Flex	★	★
Continuous Flex	★	★
<b>STANDARDS, AGENCY AND ENVIRONMENTAL COMPLIANCE</b>		
UL	✓	✓
ANSI	✓	✓
CE	✓	✓
NEC®	NFPA 70	NFPA 70
NFPA	✓	✓
RoHS2	✓	✓
REACH	✓	✓

### STANDARDS, AGENCY AND ENVIRONMENTAL COMPLIANCE:



- KEY:
- Not Applicable
  - ✓ Featured
  - ★ Cost Competitive Custom Options Available