



NWI DIRECT
In Stock. Buy Now!

NWI EXPRESS
5 Days Design to Deliver

	General Purpose	Exposed Run	Direct Burial
FEATURES			
Signal	✓	✓	✓
Control	✓	✓	✓
Instrumentation	✓	✓	✓
Power	✓	✓	✓
FLEXIBILITY			
Bend Flex	✓	✓	✓
ATTRIBUTES			
Low-Temperature Rating	≤ -20°C	≤ -20°C	≤ -20°C
High-Temperature Rating	105°C	105°C	105°C
Cold Bend	✓	✓	✓
Impact Resistant	–	✓	–
Crush Resistant	–	✓	✓
Flame Resistant	FT4/IEEE1202, UL1685 Vertical-Tray	FT4/IEEE1202, UL1685 Vertical-Tray	FT4/IEEE1202, UL1685 Vertical-Tray
Exposed Run Rated	–	✓	✓
Hazardous	Class I, Div 2	Class I, Div 2	Class I, Div 2
Direct Burial Rated	–	–	✓
Wet Location Use	★	★	★
Oil Resistant	★	★	★
Chemical Resistant	✓	✓	✓
Sunlight/UV Resistant	✓	✓	✓
Weld Slag Resistant	★	★	★
STANDARDS, AGENCY AND ENVIRONMENTAL COMPLIANCE			
UL	✓	✓	✓
ANSI	✓	✓	✓
CE	✓	✓	✓
NEC®	Article 727	Article 727	Article 727
NFPA 79	–	–	–
RoHS2	✓	✓	✓
REACH	★	★	★
PRODUCT SPECIFICATIONS			
FOUNDATION™ fieldbus	✓	✓	✓
ODVA™	✓	✓	✓
DeviceNet™	✓	✓	✓
PROFIBUS® DP and PA	✓	✓	✓
PROFINET®	✓	✓	✓
AS-i®	✓	✓	✓
CC-Link®	✓	✓	✓
CANopen®	✓	✓	✓
CAN-Bus®	✓	✓	✓
HART®	✓	✓	✓

KEY:
 – Not Applicable
 ✓ Featured
 ★ Cost Competitive Custom Options Available

FLEX: EXTREME ENGINEERING:



Products
AGENCY STANDARDS