



NWI DIRECT
In Stock. Buy Now!

NWI EXPRESS
5 Days Design to Deliver

Exposed Run		Direct Burial	
XLPE	PVC/Nylon	XLPE	PVC/Nylon
All sizes .020 (0.51)	22-20 .015 / .005 (.38 / .13) 19-15 .015 / .005 (.38 / .13) 14-12 .015 / .005 (.38 / .13)	All sizes .020 (0.51)	22-20 .015 / .005 (.38 / .13) 19-15 .015 / .005 (.38 / .13) 14-12 .015 / .005 (.38 / .13)
2 or more	2 or more	2 or more	2 or more
22-12 (.325 - 3.309)	22-12 (.325 - 3.309)	22-12 (.325 - 3.309)	22-12 (.325 - 3.309)
★	★	★	★
★	★	★	★
★	★	★	★
★	★	★	★
★	★	★	★
★	★	★	★
★	★	★	★
PVC or TPE	PVC or TPE	PVC or TPE	PVC or TPE
★	★	★	★
Determined by AWG size and number of conductors	Determined by AWG size and number of conductors	Determined by AWG size and number of conductors	Determined by AWG size and number of conductors
150V	150V	150V	150V
UL 2250, tables 11.1 & 11.2	UL 2250, tables 11.1 & 11.2	UL 2250, tables 11.1 & 11.2	UL 2250, tables 11.1 & 11.2
5 amp max	5 amp max	5 amp max	5 amp max

FLEX: EXTREME ENGINEERING:



Products
AGENCY STANDARDS