

UL 1426 | Electrical Cables for Boats

Marine Grade. Extreme Flex.

Meets or exceeds U.S. Coast Guard and American Bureau of Shipping regulations. Our extremely flexible, flame, oil and water resistant UL 1426 cables and retractiles are very easy to work with and available in flat, round, and oval shapes.

	TW, THW, THW-2, THHW	THWN, THWN-2, THHN
FEATURES		
Power	✓	✓
ATTRIBUTES		
Low-Temperature Rating	≤ -25°C	≤ -25°C
High-Temperature Rating	105°C (60°C to 90°C wet)	105°C (60°C to 90°C wet)
Cold Bend	≤ -25°C	≤ -25°C
Flame Resistant	UL 1581 Section 1061, VW-1, FT2	UL 1581 Section 1061, VW-1, FT2
Wet Location Use	✓	✓
Oil Resistant	I	I
FLEXIBILITY		
Torsional Flex	★	★
Rolling Flex	★	★
Variable Flex	★	★
Bend Flex	★	★
Continuous Flex	★	★
STANDARDS, AGENCY AND ENVIRONMENTAL COMPLIANCE		
UL	✓	✓
ANSI	✓	✓
CE	✓	✓
NEC®	Article 310 and 400	Article 310 and 400
NFPA 70	✓	✓
ABS	✓	✓
USCG	✓	✓
RoHS2	✓	✓
REACH	✓	✓

*Not applicable for single conductor

STANDARDS, AGENCY AND ENVIRONMENTAL COMPLIANCE:



ANSI CE

NEC®
ARTICLE
310 & 400



ABS USCG



REACH

KEY:

— Not Applicable

✓ Featured

★ Cost Competitive Custom Options Available